



Product Data Sheet

Reflektorové LED svítidlo

SHYLUX LED OUTLINE
SL3210B-4 8W 100-
240VAC 2° 4000K IP65



Order number

912600390

Unit EAN13 code

8595209945501

General information

Model/Description	Nástěnné svítidlo
Brand/Manufacturer	SHYLUX
Lamp type	LED
Type of luminaire	Svítidlo s krytem
Nominal voltage (V)	230 - 240 V
Degree of protection (IP)	IP65
Suitable for number of lamps	4
Suitable for wall mounting	Ano
Název položky	SHYLUX LED OUTLINE SL3210B-4 8W 100-240VAC 2° 4000K

Electrical characteristics

Rated power (W)	8 W
Lamp power	8 W
Circuit	Paralelně-kompenzační
Voltage type	AC

Working conditions

Maximum permitted storage temperature	80 °C
Burning position	Libovolná
Application	Designové osvětlení
Ambient temperature	-25/+50 °C
Applicable with movement sensor	Ano
Fire resistance "F"	Ano
Direct-/indirect proportion separately switchable	Ano

Physical characteristics

Type of chip	CREE
Packing method	1
Width	129 mm
Colour housing	Stříbrná
Length	129 mm
Height/depth (mm)	71 mm
Material housing	Aluminium
Colour cover	Aluminium
Material cover	Ostatní
Impact strength	IK10
Type of surface	Matný
Number of LEDs	4

EuP Parameters

Average Lifetime B50 (h)	50000 h
Colour difference	0,8 %
Rated service life	50000 h

Additional information

With lamp	Ano
-----------	-----

Lighting characteristics

Light Colour	chladná bílá
Colour temperature	4000 K
Colour of light	740
Anti-glare limiting UGR lengthwise	20
Anti-glare limiting UGR crosswise	20
Direct-/indirect proportion separately controllable	Ano
Light outlet	Přímé
Light sharing	Symetrické
Beam angle Degrees (°)	2 °

Safety information

Safety instructions	www.nbb.cz
Protection class	Ochranným vodičem

Environmental characteristics

Mercury content	0,00 mg
-----------------	---------

Exclusion of liability

Changes to data are subject to prior notice. NBB Bohemia s.r.o. accepts no responsibility for damages caused by inaccurate interpretation of the content on this site.

Notice

Under the scope of Act 185/2001 Coll. as amended, this product is included in waste group 5 (light sources and luminaires). In view of the harmful effects of mercury on the environment and on human health, the creators of group 5 waste (consumers) are obliged to dispose of used light sources for recycling. Do not throw this product into mixed waste after use. Take it to the

nearest store, collection yard, or other designated location for free recycling. You can also dispose of the used products for recycling in our sales outlets or in collection points of collective recycling systems or municipal collection yards. Ecological recycling of waste electrical and electronic equipment is ensured through the RETELA collective system (www.retela.cz).

Notice

Single LED chip failure, luminous flux deviation +/- 10% as well as chromaticity deviation +/- 150K are in compliance with applicable standards and are not a reason for complaint.

Popis

NBB Bohemia s.r.o., Sídliště 693, 407 22 Benešov nad Ploučnicí
<https://www.nbb.cz/en/> | hotmail@nbb.cz

Copyright CE 2024 NBB Bohemia s.r.o. Všechna práva vyhrazena.