



Product Data Sheet

LED svítidlo podhledové

RIKI LED PANEL 30W
□ 600x300mm 100-240V
4000K dimmable IP44



Order number

253400075

Unit EAN13 code

8595209924193

General information

Model/Description	Podhledová panelová svítidla
Finish	Vestavné/Recessed
Brand/Manufacturer	NBB
Material	Aluminium/PS
Lamp type	LED
Nominal service life (h)	35000 h
Degree of protection (IP)	IP44
Dimmable	Ano
With light sensor	ne
Suitable for suspended mounting	ne
Lamp type	LED
Nominal voltage (V)	100 - 265 V
Degree of protection (IP)	IP40
Suitable for number of lamps	1
Suitable for wall mounting	Ne
Suitable for built-in mounting	Ano
Suitable for surface mounting	Ne
Suitable for ceiling mounting	Ano
Název položky	RIKI LED PANEL 30W □ 596x297mm 100-240V 4000K stmívatelný IP4

Electrical characteristics

Nominal wattage	30 W
Rated power (W)	30,0 W
Operating voltage (V)	100 - 240 V
Endurance	265 V

Type of Voltage	AC
Lowest permitted operating voltage (V)	100 V
Direct connection to the mains	Ne
Nominal current	160 mA
Lamp power	30 W
Voltage type	AC
Suitable for lamp power	30 W
Nominal current (A)	0,160 A
System power	30 W

Working conditions

Average lifetime of the ballast (h)	35000 h
Integrated driver	Ne
Maximum permitted storage temperature	80 °C
Type of cooler	Aluminium
Burning position	Universal
Application	Všeobecné osvětlování
With movement sensor	ne
Suitable for frequent switching	Ano
Ambient temperature	-20/+45 °C
Applicable with movement sensor	Ano
Fire resistance "D"	ne
Fit for monitor workplace	Ne
Driver included	Ano

Mounting methods/application

Mounting method	Vestavná montáž
Dimensions of installation hole	600x300 mm
Mounting method	Vestavná

Physical characteristics

Type of chip	Epistar
Dimensions (mm)	596x297x9 mm
Packing method	5 - 1
Weight gross	2,3 g
Width	297 mm
Colour housing	Stříbrná
Weight netto	3155 g
Length	596 mm
Height/depth (mm)	9 mm
Material housing	Aluminium
Material cover	Opálový/Matný plast
Impact strength	IK06
Type of surface	Matný
Number of LEDs	150
Adjustability	Pevné nenastavitelné

EuP Parameters

Average Lifetime B50 (h)	35000 h
Luminescence Life maintenance factor	80,0 %
Factor of functional reliability (LSF) after nom. life	50,0 %
Time to 60 % luminous flux	0,25 s
Number of maximal switching cycles	>50000
The rate of premature failures	<0,1 %
Rated service life	35000 h
Energy consumption (AGGR)	33 kWh/1000h
Turn-on time	<0,3 s
GLS replacement	162 W

Additional information

Note	24 - 7
With lamp	ano

Lighting characteristics

Color rendering	1B
Light Colour	Chladná bílá
Wavelength range	400 - 700 nm
Dominant wavelength	595 nm
Luminous flux	2700 lm
Colour temperature	4000 K
Colour rendering index CRI	80 Ra
Colour of light	840
Light outlet	Přímé
Light sharing	Symetrické
Radiation angle	Extrémně široký úhel >80°
Colour temperature	3700 - 4000 K
Effective luminous flux	2700 lm
Colour	Bílá
Beam angle Degrees (°)	120 °
Chromaticity coordinates x	0,3966
Chromaticity coordinates y	0,3939

Safety information

Insulation class	Třída II
Safety instructions	www.nbb.cz
Protection class	Dvojitou izolací

Environmental characteristics

Mercury content	0,00 mg
-----------------	---------

Energetic characteristics

Lamp Power factor (PF)	>0.9
Rated efficiency after 100h	99,9 %

Exclusion of liability

Changes to data are subject to prior notice. NBB Bohemia s.r.o. accepts no responsibility for damages caused by inaccurate interpretation of the content on this site.

Notice

Under the scope of Act 185/2001 Coll. as amended, this product is included in waste group 5 (light sources and luminaires). In view of the harmful effects of mercury on the environment and on human health, the creators of group 5 waste (consumers) are obliged to dispose of used light sources for recycling. Do not throw this product into mixed waste after use. Take it to the nearest store, collection yard, or other designated location for free recycling. You can also dispose of the used products for recycling in our sales outlets or in collection points of collective recycling systems or municipal collection yards. Ecological recycling of waste electrical and electronic equipment is ensured through the RETELA collective system (www.retela.cz).

Notice

Single LED chip failure, luminous flux deviation +/- 10% as well as chromaticity deviation +/- 150K are in compliance with applicable standards and are not a reason for complaint.

Popis

NBB Bohemia s.r.o., Sídliště 693, 407 22 Benešov nad Ploučnicí
<https://www.nbb.cz/en/> | hotmail@nbb.cz

Copyright CE 2024 NBB Bohemia s.r.o. Všechna práva vyhrazena.