



NBB Bohemia s.r.o.

Výroba a prodej osvětlovací techniky, Sídliště 693, 407 22 Benešov nad Ploučnicí



Product Data Sheet

Svítlidlo Ø 400 mm SKLO + plech.montura

**KAROLINA LED 240V
24W/830 OPÁL EM3h
IP44**



Order number

908070196

Unit EAN13 code

8595209970695

General information

Finish	Přisazené/Wall mounted
Brand/Manufacturer	NBB
Lamp type	LED
Nominal service life (h)	25000 h
Time of emergency operation	1 h
Degree of protection (IP)	IP44
Dimmable	Ne
Autonomy	1 h
Labelling type	Trvalý
Lamp type	LED
Type of luminaire	Svítlidlo s krytem
Nominal voltage (V)	230 - 240 V
Degree of protection (IP)	IP20
Suitable for number of lamps	1
Suitable for wall mounting	Ano
Dimmable by conventional dimmers	Ne
Název položky	KAROLINA LED 240V 24W/830 OPÁL EM1h IP44
Typ nouzového provozu	Trvalý

Electrical characteristics

Nominal wattage	24 W
Operating voltage (V)	200 - 240 V
Voltage battery	3,6 V
Nominal current	218 mA
Lamp power	24 W

Circuit	Paralelně-kompenzační
Power	24 W
Voltage type	AC
Frequency	50 - 60 Hz
Nominal current (A)	0,11 A
Total power (W) (light fitting)	24 W

Working conditions

Charging time	24 h
Operating frequency	50 - 60 Hz
Battery type	NiCD
charging control	Yes
Battery capacity	4000 mAh
Light source is part of the fixture	Yes
Maximum permitted storage temperature	80 °C
Burning position	Libovolná
Installation height (m)	2 - 4 m
Application	Všeobecné osvětlování
Suitable for through-wiring	Ano
Type of control gear	Elektronický nestmívatelný
Ambient temperature	-20/+40 °C
Suitable for emergency lighting	Ano
Fire resistance "F"	Ano
Fit for monitor workplace	Ano
Driver included	Ano

Physical characteristics

Dimensions (mm)	Ø400 x 125 mm
Packing method	1
Outer diameter	400 mm
Reflector	Bílý
Colour housing	Bílá
Weight netto	1700 g
Height/depth (mm)	125 mm
Material housing	Ocelový plech
Colour cover	Bílá
Material cover	Opálové sklo
Impact strength	IK05
Number of LEDs	

EuP Parameters

Average lifetime of the light source (h)	25000 h
Luminescence Life maintenance factor	80 %
Factor of functional reliability (LSF) after nom. life	50 %
Number of maximal switching cycles	>250000
The rate of premature failures	>1 %
Rated service life	25000 h

Energy consumption (AGGR)	27,50 kWh/1000h
---------------------------	-----------------

Equivalent linear fluorescent	30 W
-------------------------------	------

Additional information

With lamp	Ano
-----------	-----

Lighting characteristics

Color rendering	1B
-----------------	----

Light Colour	teplá bílá
--------------	------------

Wavelength range	400 - 780 nm
------------------	--------------

Dominant wavelength	582 nm
---------------------	--------

Luminous flux	2190 lm
---------------	---------

Colour temperature	3000 K
--------------------	--------

Colour rendering index CRI	83 Ra
----------------------------	-------

Colour of light	830
-----------------	-----

Anti-glare limiting UGR lengthwise	20
------------------------------------	----

Anti-glare limiting UGR crosswise	20
-----------------------------------	----

Direct-/indirect proportion separately controllable	Ano
---	-----

Light outlet	Přímé
--------------	-------

Light sharing	Symetrické
---------------	------------

Colour temperature	3000 - 3200 K
--------------------	---------------

Effective luminous flux	2190 lm
-------------------------	---------

Chromaticity coordinates x	0,423
----------------------------	-------

Chromaticity coordinates y	0,398
----------------------------	-------

Safety information

Insulation class	Třída I
------------------	---------

Safety instructions	www.nbb.cz
---------------------	------------

Protection class	Ochranným vodičem
------------------	-------------------

Energetic characteristics

Lamp Power factor (PF)	0,7
------------------------	-----

Lamp efficacy	91,25 lm/W
---------------	------------

Exclusion of liability

Changes to data are subject to prior notice. NBB Bohemia s.r.o. accepts no responsibility for damages caused by inaccurate interpretation of the content on this site.

Notice

Under the scope of Act 185/2001 Coll. as amended, this product is included in waste group 5 (light sources and luminaires). In view of the harmful effects of mercury on the environment and on human health, the creators of group 5 waste (consumers) are obliged to dispose of used light sources for recycling. Do not throw this product into mixed waste after use. Take it to the nearest store, collection yard, or other designated location for free recycling. You can also dispose of the used products for recycling in our sales outlets or in collection points of collective recycling systems or municipal collection yards. Ecological recycling of waste electrical and electronic equipment is ensured through the RETELA collective system (www.retela.cz).

Notice (LVD)

LED light sources ranks among electrotechnical products powered by mains 230-240V. For safety reasons, it is recommended that the assembly, connection or disassembly be carried out by a person with an appropriate electrotechnical qualification. When installing or disassembling, it is advisable to disconnect the power supply otherwise there may be a risk of electric shock. Only use the product in the luminaires designed for this type of light source. The manufacturer can not be held responsible for

damages resulting from inappropriate connection, connection to an unsuitable distribution system, or damages resulting from mechanical damage to the light source. Observe the operating values on the product. Do not expose the product to inappropriate weathering or high temperatures unless it is expressly stated that the product is intended to be operated under these conditions. When installing, wiring or disassembling, follow the generally accepted safety precautions.

Notice

Single LED chip failure, luminous flux deviation +/- 10% as well as chromaticity deviation +/- 150K are in compliance with applicable standards and are not a reason for complaint.

If the luminaire contains batteries

If the luminaire contains rechargeable rechargeable batteries for emergency operation, we provide a 6 months warranty for these batteries from the date of commissioning. This warranty period is valid for both B2C and B2B customers.

Popis

LED luminaire with glass opal cover Ø 400mm with emergency module. The luminaire has a metal mount for mounting on a wall or ceiling. Cover IP44, suitable for use in corridors, waiting rooms, etc. Color temperature 3000K (warm white). Effective luminous flux 2190lm.

NBB Bohemia s.r.o., Sídliště 693, 407 22 Benešov nad Ploučnicí
<https://www.nbb.cz/en/> | hotmail@nbb.cz

Copyright CE 2024 NBB Bohemia s.r.o Všechna práva vyhrazena.