



**NBB Bohemia s.r.o.**

Výroba a prodej osvětlovací techniky, Sídliště 693, 407 22 Benešov nad Ploučnicí

## Product Data Sheet

Nouzové svítidlo nástěnné (tabulka s piktogramem) - osvětlení únikové cesty

## ESCAPO-W 20LED 230-240V TP/DP EM3h IP20 nástěnné



Order number  
**910122020**

Unit EAN13 code  
**8595209953797**

### General information

Finish	Emergency LED light with pictogram
Brand/Manufacturer	NBB
Material	plast
Nominal service life (h)	30000 h
Degree of protection (IP)	IP20
Autonomy	3 h
Power supply system	Vlastní baterie
Labelling type	Vkládací fólie
Type of indicator	Jednostranný/Oboustranný
Lamp type	LED
Wiring system	Trvalý provoz
Nominal voltage (V)	230 - 240 V
Degree of protection (IP)	IP20
Název položky	ESCAPO-W 20LED 230-240V TP EM3h IP20

### Electrical characteristics

Nominal wattage	3 W
Standby power (W)	3 W
Operating voltage (V)	190 - 240 V
Type of Voltage	AC
Voltage battery	3,6 V
Lamp power	3 W
Circuit	Paralelně kompenzační
Voltage type	AC
Luminous flux at emergency operation	60 lm

Recognition distance	24 m
Nominal current (A)	0,080 A

#### Working conditions

Battery Life	1000 cyklů
Charging time	24 h
Operating frequency	50 - 60 Hz
Battery type	NiCD
charging control	Ano
Battery capacity	1200 mAh
Permanent connection to mains supply	Ano
Burning position	Svislá
Application	Orientační systémy
Ambient temperature	5 - 40 °C

#### Mounting methods/application

Mounting method	Nástěnná
-----------------	----------

#### Physical characteristics

Type of chip	SMD 2835
Dimensions (mm)	390 x 190 x 30 mm
Packing method	1
Weight gross	1000 g
Width	30 mm
Colour housing	Bílá
Weight netto	851 g
Length	390 mm
Height/depth (mm)	190 mm
Material housing	Plast
Material cover	Transparentní plast
Monitoring equipment	Testovací tlačítko
Number of LEDs	20

#### EuP Parameters

Average Lifetime B50 (h)	30000 h
Number of maximal switching cycles	50000
Rated service life	30000 h
Turn-on time	<1 s

#### Additional information

Battery quality	NiCd
With lamp	Ano

#### Lighting characteristics

Light Colour	Chladná denní
Dominant wavelength	456 nm
Colour temperature	6500 K

Colour rendering index CRI	80 Ra
Colour temperature	6000 - 7000 K
Effective luminous flux	60 lm
Colour	Bílá
Chromaticity coordinates x	0,320
Chromaticity coordinates y	0,340

### Safety information

Insulation class	Třída I
Safety instructions	<a href="http://www.nbb.cz">www.nbb.cz</a>
Protection class	Ochranným vodičem

### Energetic characteristics

Lamp Power factor (PF)	<0,5
------------------------	------

### Exclusion of liability

Changes to data are subject to prior notice. NBB Bohemia s.r.o. accepts no responsibility for damages caused by inaccurate interpretation of the content on this site.

### Notice

Under the scope of Act 185/2001 Coll. as amended, this product is included in waste group 5 (light sources and luminaires). In view of the harmful effects of mercury on the environment and on human health, the creators of group 5 waste (consumers) are obliged to dispose of used light sources for recycling. Do not throw this product into mixed waste after use. Take it to the nearest store, collection yard, or other designated location for free recycling. You can also dispose of the used products for recycling in our sales outlets or in collection points of collective recycling systems or municipal collection yards. Ecological recycling of waste electrical and electronic equipment is ensured through the RETELA collective system ([www.retela.cz](http://www.retela.cz)).

### Notice (LVD)

LED light sources ranks among electrotechnical products powered by mains 230-240V. For safety reasons, it is recommended that the assembly, connection or disassembly be carried out by a person with an appropriate electrotechnical qualification. When installing or disassembling, it is advisable to disconnect the power supply otherwise there may be a risk of electric shock. Only use the product in the luminaires designed for this type of light source. The manufacturer can not be held responsible for damages resulting from inappropriate connection, connection to an unsuitable distribution system, or damages resulting from mechanical damage to the light source. Observe the operating values on the product. Do not expose the product to inappropriate weathering or high temperatures unless it is expressly stated that the product is intended to be operated under these conditions. When installing, wiring or disassembling, follow the generally accepted safety precautions.

### Notice

Single LED chip failure, luminous flux deviation +/- 10% as well as chromaticity deviation +/- 150K are in compliance with applicable standards and are not a reason for complaint.

### If the luminaire contains batteries

If the luminaire contains rechargeable rechargeable batteries for emergency operation, we provide a 6 months warranty for these batteries from the date of commissioning. This warranty period is valid for both B2C and B2B customers.

### Notice

This product ranks among electrotechnical products powered by mains voltage 230-240V. For safety reasons, it is recommended that the assembly, connection or disassembly be carried out by a person with an appropriate electrotechnical qualification. Please note that the product may only be put into service with original covers, otherwise there may be a risk of electric shock, especially from the terminal block. Only use the product in places that are suitable for this purpose; do not use products intended for indoor use only in the outdoor environment. When installing or dismantling an emergency luminaire, we recommend disconnecting the power supply otherwise there may be a risk of electric shock. Observe the prescribed position when operating the product and how it is attached. Only connect the product to the rated voltage, or load it only to the maximum permitted power. Install only light sources for this type of luminaire. The manufacturer can not be held responsible for damages resulting from inappropriate connection, connection to an unsuitable distribution system, or damage resulting from the use of

an unsuitable light source. Observe the operating values on the label. Do not expose the product to inappropriate weathering or high temperatures unless it is expressly stated that the product is intended to be operated under these conditions. When installing, wiring or disassembling, follow the generally accepted safety precautions.

**NOTICE:**

The emergency luminaire is energized even after disconnecting the power supply due to its own charged batteries. Therefore, it is recommended that the installation and disassembly be carried out only by a person with the appropriate electrotechnical qualifications.

Do not throw the emergency luminaire into the mixed waste after use. Take it to the nearest store, collection yard, or other designated location for free recycling. You can also deliver the used luminaires for recycling at our sales outlets. Emergency lights and modules contain a rechargeable battery. You can find the list of collection points on the Retel and Ekolamp Collective Systems pages.

**Popis**

**NBB Bohemia s.r.o., Sídliště 693, 407 22 Benešov nad Ploučnicí**

<https://www.nbb.cz/en/> | [hotmail@nbb.cz](mailto:hotmail@nbb.cz)

Copyright CE 2024 NBB Bohemia s.r.o. Všechna práva vyhrazena.