



NBB Bohemia s.r.o.

Výroba a prodej osvětlovací techniky, Sídliště 693, 407 22 Benešov nad Ploučnicí



Product Data Sheet

LED závěsné světlo P05

Led drop light P05-42-3090



Order number

253467080

Unit EAN13 code

8595209970022

General information

Model/Description	LED svítidlo
Finish	Závěsné
Brand/Manufacturer	GRACION
Nominal service life (h)	50000 h
Degree of protection (IP)	IP20
Dimmable	Ne
Lamp type	LED
Electrical connection with connector system	Ano
Nominal voltage (V)	230 - 240 V
Degree of protection (IP)	IP20
Suitable for number of lamps	1
Suitable for ceiling mounting	Ano
Dimmable by conventional dimmers	Ne
Název položky	Led drop light P05-42-3090

Electrical characteristics

Nominal wattage	42 W
Rated power (W)	42 W
Operating voltage (V)	100 - 240 V
Type of Voltage	AC
Lowest permitted operating voltage (V)	220 V
Lamp power	42 W
Voltage type	AC
System power	42 W

Working conditions

Integrated driver	Ne
Light source is part of the fixture	Ano
Maximum permitted storage temperature	80 °C
Burning position	Vertikální
Application	Všeobecné osvětlování
Type of control gear	LED driver CC
Suitable for frequent switching	Ano
Ambient temperature	-20/+40 °C
Fire resistance "F"	Ano
Suspension supplied with the product	Ano
Fit for monitor workplace	Ano
Driver included	Ano

Physical characteristics

Dimensions (mm)	Ø361 x 407 mm
Packing method	1
Outer diameter	361 mm
Height	407 mm
Colour housing	Černá
Material housing	Aluminium
Type of surface	Matný
Number of LEDs	1

EuP Parameters

Average Lifetime B50 (h)	50000 h
Luminescence Life maintenance factor	80 %
Factor of functional reliability (LSF) after nom. life	50 %
Number of maximal switching cycles	>250000
The rate of premature failures	<1 %
Colour difference	90 %
Rated service life	50000 h
Energy consumption (AGGR)	42 kWh/1000h
Turn-on time	<0,2 s

Additional information

With lamp	Ano
-----------	-----

Lighting characteristics

Light Colour	teplá bílá
Wavelength range	400 - 800 nm
Luminous flux	4900 lm
Colour temperature	3000 K
Radiation angle	24 °
Colour rendering index CRI	90 Ra
Colour of light	930

Anti-glare limiting UGR lengthwise	19
Anti-glare limiting UGR crosswise	19
Light outlet	Přímé
Light sharing	Symetrické
Radiation angle	Střední úhel 21-40°
Colour temperature	2900 - 3200 K
Effective luminous flux	4900 lm
Colour	Bílá
Beam angle Degrees (°)	24 °

Safety information

Insulation class	Třída II
Safety instructions	www.nbb.cz
Protection class	Ochranným vodičem

Energetic characteristics

Lamp Power factor (PF)	0,99
Rated efficiency after 100h	99,99 %
Lamp efficacy	98,80 lm/W

Popis

NBB Bohemia s.r.o., Sídliště 693, 407 22 Benešov nad Ploučnicí
<https://www.nbb.cz/en/> | hotmail@nbb.cz

Copyright CE 2024 NBB Bohemia s.r.o Všechna práva vyhrazena.