



## Product Data Sheet



LED svítidlo do velké výšky, komponenty  
TRIDONIC

**RAMUNE (UFO) LED**  
**200W 220-240V AC IP67**  
**RM-EN1/1L/26000**  
**TRIDONIC**  
**390\*390\*200mm**

Order number  
**253231015**

### General information

|                              |             |
|------------------------------|-------------|
| Specifications               | 1           |
| Brand/Manufacturer           | Ecolight    |
| Lamp type                    | Ostatní     |
| Nominal voltage (V)          | 220 - 240 V |
| Degree of protection (IP)    | IP67        |
| Suitable for number of lamps | 1           |
| Název položky                | 1           |

### Electrical characteristics

|                     |       |
|---------------------|-------|
| Lamp power          | 200 W |
| Voltage type        | AC    |
| Nominal current (A) | A A   |

### Working conditions

|                                       |                            |
|---------------------------------------|----------------------------|
| Maximum permitted storage temperature | 60 °C                      |
| Type of control gear                  | Elektronický nestmívatelný |
| Ambient temperature                   | -25/+45 °C                 |
| Suitable for emergency lighting       | Ne                         |
| Fire resistance "D"                   | Ano                        |
| Type of dimming                       | Nestmívatelné              |
| Driver included                       | Ano                        |
| Optimální instalační výška do         | 12 m                       |

### Mounting methods/application

|                 |         |
|-----------------|---------|
| Mounting method | Závěsná |
|-----------------|---------|

**Physical characteristics**

|                   |           |
|-------------------|-----------|
| Colour housing    | Černá     |
| Diameter          | 390 mm    |
| Ball-proof        | Ano       |
| Length            | l (mm) mm |
| Height/depth (mm) | 180 mm    |
| Material housing  | Aluminium |
| Impact strength   | IK08      |

**EuP Parameters**

|                    |         |
|--------------------|---------|
| Rated service life | 50000 h |
|--------------------|---------|

**Additional information**

|           |     |
|-----------|-----|
| With lamp | Ano |
|-----------|-----|

**Lighting characteristics**

|   |               |
|---|---------------|
| Colour temperature                                  | 4000 K        |
| Colour rendering index CRI                          | CRI (Ra) Ra   |
| Direct-/indirect proportion separately controllable | Ano           |
| Light outlet  | Přímé         |
| Light sharing                                       | Široký úhel   |
| Colour temperature                                  | 4000 - 4200 K |
| Effective luminous flux                             | 23436 lm      |
| Colour  | Bílá          |

**Safety information**

|                  |                   |
|------------------|-------------------|
| Protection class | Ochranným vodičem |
|------------------|-------------------|

**Energetic characteristics**

|               |          |
|---------------|----------|
| Lamp efficacy | 126 lm/W |
|---------------|----------|

**Exclusion of liability**

Changes to data are subject to prior notice. NBB Bohemia s.r.o. accepts no responsibility for damages caused by inaccurate interpretation of the content on this site.

**Notice**

Under the scope of Act 185/2001 Coll. as amended, this product is included in waste group 5 (light sources and luminaires). In view of the harmful effects of mercury on the environment and on human health, the creators of group 5 waste (consumers) are obliged to dispose of used light sources for recycling. Do not throw this product into mixed waste after use. Take it to the nearest store, collection yard, or other designated location for free recycling. You can also dispose of the used products for recycling in our sales outlets or in collection points of collective recycling systems or municipal collection yards. Ecological recycling of waste electrical and electronic equipment is ensured through the RETELA collective system ([www.retela.cz](http://www.retela.cz)).

**Notice (LVD)**

LED light sources ranks among electrotechnical products powered by mains 230-240V. For safety reasons, it is recommended that the assembly, connection or disassembly be carried out by a person with an appropriate electrotechnical qualification. When installing or disassembling, it is advisable to disconnect the power supply otherwise there may be a risk of electric shock. Only use the product in the luminaires designed for this type of light source. The manufacturer can not be held responsible for damages resulting from inappropriate connection, connection to an unsuitable distribution system, or damages resulting from mechanical damage to the light source. Observe the operating values on the product. Do not expose the product to inappropriate weathering or high temperatures unless it is expressly stated that the product is intended to be operated under

these conditions. When installing, wiring or disassembling, follow the generally accepted safety precautions.

#### **Notice**

Single LED chip failure, luminous flux deviation +/- 10% as well as chromaticity deviation +/- 150K are in compliance with applicable standards and are not a reason for complaint.

#### **Popis**

**NBB Bohemia s.r.o., Sídliště 693, 407 22 Benešov nad Ploučnicí**  
<https://www.nbb.cz/en/> | [hotmail@nbb.cz](mailto:hotmail@nbb.cz)

Copyright CE 2024 NBB Bohemia s.r.o Všechna práva vyhrazena.