



Product Data Sheet

Kancelářské LED svítidlo

TAUR LED 35W/840
1L/150 IP20 PAR



Order number

910710105

Unit EAN13 code

8595209953384

General information

Model/Description	Zářivkové svítidlo
Finish	LED PAR
Brand/Manufacturer	NBB
Material	Plech
Lamp type	LED
Nominal service life (h)	30000 h
Degree of protection (IP)	IP20
Dimmable	Ne
Lamp type	LED
Nominal voltage (V)	230 - 240 V
Degree of protection (IP)	IP20
Suitable for number of lamps	2
Dimmable by conventional dimmers	Ne
Název položky	TAUR LED 35W/840 1L/150 IP20 PAR

Electrical characteristics

Nominal wattage	35 W
Operating voltage (V)	220 - 240 V
Type of Voltage	AC
Lamp power	35 W
Circuit	Paralelně-kompenzační
Voltage type	AC
Lamp power at multiwatt	Ostatní

Working conditions

Operating frequency	50 - 60 Hz
Light source is part of the fixture	ano
Protection against overvoltage	Ano
Burning position	Horizontální
Installation height (m)	2 - 4 m
Application	Všeobecné osvětlování/General lighting
Suitable for through-wiring	Ne
Type of control gear	Elektronický nestmívatelný
Suitable for light line configuration	Ne
Suitable for emergency lighting	Ne
Fire resistance "D"	Ano
Suspension supplied with the product	Ano
Fit for monitor workplace	Ano
Type of dimming	Nestmívatelné
Emergency unit integrated	Ne
Driver included	ano

Physical characteristics

Numbers of ballasts	1
Dimensions (mm)	1490 x 144 x 114 mm
Weight gross	3550 g
Width	144 mm
Reflector	Vysoce leštěný
Height	114 mm
Colour housing	Stříbrná
Weight netto	3170 g
Type of grid	Vysoce leštěná
Length	1539 mm
Material housing	Aluminium
Impact strength	IK06
Type of surface	Matný

EuP Parameters

Average Lifetime B50 (h)	30000 h
The rate of premature failures	<1 %

Additional information

With lamp	Ne
-----------	----

Lighting characteristics

Color rendering	840
Light Colour	chladná bílá
Light outlet	Přímé
Luminous flux light source	3600 lm

Safety information

Insulation class	třída I
------------------	---------

Safety instructions

www.nbb.cz

Protection class

Ochranným vodičem

Energetic characteristics

Lamp Power factor (PF)

0,98

Exclusion of liability

Changes to data are subject to prior notice. NBB Bohemia s.r.o. accepts no responsibility for damages caused by inaccurate interpretation of the content on this site.

Notice

Under the scope of Act 185/2001 Coll. as amended, this product is included in waste group 5 (light sources and luminaires). In view of the harmful effects of mercury on the environment and on human health, the creators of group 5 waste (consumers) are obliged to dispose of used light sources for recycling. Do not throw this product into mixed waste after use. Take it to the nearest store, collection yard, or other designated location for free recycling. You can also dispose of the used products for recycling in our sales outlets or in collection points of collective recycling systems or municipal collection yards. Ecological recycling of waste electrical and electronic equipment is ensured through the RETELA collective system (www.retela.cz).

Notice

Single LED chip failure, luminous flux deviation +/- 10% as well as chromaticity deviation +/- 150K are in compliance with applicable standards and are not a reason for complaint.

Popis

LED office luminaire, low glare factor UGR <19, Ra> 80, optional emergency module, hanging mounting. Length 1540 mm.

NBB Bohemia s.r.o., Sídliště 693, 407 22 Benešov nad Ploučnicí
<https://www.nbb.cz/en/> | hotmail@nbb.cz

Copyright CE 2024 NBB Bohemia s.r.o Všechna práva vyhrazena.