



NBB Bohemia s.r.o.

Výroba a prodej osvětlovací techniky, Sídliště 693, 407 22 Benešov nad Ploučnicí



Product Data Sheet

Kancelářské LED svítidlo

**TAUR LED 35W/830
1L/150 IP20 OPAL**



Order number

910710107

Unit EAN13 code

8595209953391

General information

Model/Description

Finish

Brand/Manufacturer

Název položky

Working conditions

Dimmable range %

Maximum permitted storage temperature °C

Burning position

Ambient temperature °C

Fire resistance "F"

Driver included

Physical characteristics

Type of chip

Number of LEDs

EuP Parameters

Luminescence Life maintenance factor %

Factor of functional reliability (LSF) after nom. life %

Equivalent to fluo.lamp (W) W

Number of maximal switching cycles

Colour difference %

The light source is designed for outdoor and industrial use

Equivalent linear fluorescent W

Equivalent compact fluorescent lamps	W
Equivalent mercury lamp	W
GLS replacement	W
Φ 90°	lm

Lighting characteristics

Color rendering	
Light Colour	
Wavelength range	nm
Dominant wavelength	nm
Chromaticity coordinates x	
Chromaticity coordinates y	

Safety information

Safety instructions

Energetic characteristics

Lamp Power factor (PF)	
Lamp efficacy	lm/W

Exclusion of liability

Changes to data are subject to prior notice. NBB Bohemia s.r.o. accepts no responsibility for damages caused by inaccurate interpretation of the content on this site.

Notice

Under the scope of Act 185/2001 Coll. as amended, this product is included in waste group 5 (light sources and luminaires). In view of the harmful effects of mercury on the environment and on human health, the creators of group 5 waste (consumers) are obliged to dispose of used light sources for recycling. Do not throw this product into mixed waste after use. Take it to the nearest store, collection yard, or other designated location for free recycling. You can also dispose of the used products for recycling in our sales outlets or in collection points of collective recycling systems or municipal collection yards. Ecological recycling of waste electrical and electronic equipment is ensured through the RETELA collective system (www.retela.cz).

Notice

Single LED chip failure, luminous flux deviation +/- 10% as well as chromaticity deviation +/- 150K are in compliance with applicable standards and are not a reason for complaint.

Popis

LED office luminaire, low glare factor UGR <19, Ra> 80, optional emergency module, hanging mounting. Length 1540 mm.

NBB Bohemia s.r.o., Sídliště 693, 407 22 Benešov nad Ploučnicí
<https://www.nbb.cz/en/> | hotmail@nbb.cz

Copyright © 2024 NBB Bohemia s.r.o. Všechna práva vyhrazena.