



Product Data Sheet

LED zdroj světla kompaktní

LQ-HR LED 230-240V 18W
4000K 2G11 CL 410mm
2550lm



Order number

259200110

Unit EAN13 code

8595209953506

General information

Model/Description	LED kompaktní světelný zdroj
Brand/Manufacturer	NBB
Material	Aluminium/PC
Nominal service life (h)	30000 h
Colour	Bílá
Socket	Ostatní
Dimmable	Ne
Energy efficiency class (canceled regulation!)	A++
Nominal voltage (V)	230 - 240 V
Degree of protection (IP)	IP20
Dimmable by conventional dimmers	NE
Název položky	LQ-HR LED 230-240V 18W 4000K 2G11 CL 410mm 2550lm
Třída energetické účinnosti podle 2019/2015	D

Electrical characteristics

Nominal wattage	17,85 W
Operating voltage (V)	85 - 265 V
Type of Voltage	AC
Nominal current	118 mA
Lamp power	18 W
Voltage type	AC
Total power (W) (light fitting)	19,8 W
Elektrické parametry předřadníku	Sec. DC 75V/0,22A

Working conditions

Integrated driver	Ano
Operating frequency	50 - 60 Hz
Type of cooler	Aluminium
Burning position	Libovolná
Application	Všeobecné osvětlování

Physical characteristics

Type of chip	Epistar
Dimensions (mm)	423 x 43 x 29 mm
Width	43 mm
Height	29 mm
Diameter	29 mm
Lamp shape	Lineární
Length	423 mm
Type of glass/cover	Čirý

EuP Parameters

Average Lifetime B50 (h)	30000 h
Luminescence Life maintenance factor	70 %
Factor of functional reliability (LSF) after nom. life	50 %
Time to 60 % luminous flux	<0,3 s
Number of maximal switching cycles	>100000
The rate of premature failures	<0,1 %
Rated service life	30000 h
Energy consumption (AGGR)	18 kWh/1000h
Equivalent compact fluorescent lamps	36 W
Survival Factor	50
GLS replacement	156 W

Lighting characteristics

Light Colour	chladná bílá
Wavelength range	410 - 760 nm
Dominant wavelength	450 nm
Luminous flux	2560 lm
Colour temperature	4000 K
Colour rendering index CRI	80 Ra
Maximal intensity (Cd)	619 Cd
Colour of light	840
Light colour category	Neutrální <5300K
Beam angle Degrees (°)	140 °
Chromaticity coordinates x	0,371
Chromaticity coordinates y	0,365

Environmental characteristics

Mercury content	0,00 mg
-----------------	---------

Energetic characteristics

Lamp Power factor (PF)	0,65
Light source efficiency	85 %
Lamp efficacy	142 lm/W
Lamp displacement factor (DF)	0,94
Exclusion of liability	

Changes to data are subject to prior notice. NBB Bohemia s.r.o. accepts no responsibility for damages caused by inaccurate interpretation of the content on this site.

Notice

Under the scope of Act 185/2001 Coll. as amended, this product is included in waste group 5 (light sources and luminaires). In view of the harmful effects of mercury on the environment and on human health, the creators of group 5 waste (consumers) are obliged to dispose of used light sources for recycling. Do not throw this product into mixed waste after use. Take it to the nearest store, collection yard, or other designated location for free recycling. You can also dispose of the used products for recycling in our sales outlets or in collection points of collective recycling systems or municipal collection yards. Ecological recycling of waste electrical and electronic equipment is ensured through the RETELA collective system (www.retela.cz).

Notice (LVD)

LED light sources ranks among electrotechnical products powered by mains 230-240V. For safety reasons, it is recommended that the assembly, connection or disassembly be carried out by a person with an appropriate electrotechnical qualification. When installing or disassembling, it is advisable to disconnect the power supply otherwise there may be a risk of electric shock. Only use the product in the luminaires designed for this type of light source. The manufacturer can not be held responsible for damages resulting from inappropriate connection, connection to an unsuitable distribution system, or damages resulting from mechanical damage to the light source. Observe the operating values on the product. Do not expose the product to inappropriate weathering or high temperatures unless it is expressly stated that the product is intended to be operated under these conditions. When installing, wiring or disassembling, follow the generally accepted safety precautions.

Notice

Single LED chip failure, luminous flux deviation +/- 10% as well as chromaticity deviation +/- 150K are in compliance with applicable standards and are not a reason for complaint.

Popis

Technical drawing



