

## Product Data Sheet

LED pásek



**LED Strip 12V 60LED/m**  
**SMD5050 RGB IP65**  
**14,4W/m multichip**

Order number

**903003060**

Unit EAN13 code

**8595209916860**

### General information

|                               |   |
|-------------------------------|---|
| Model/Description             | <b>Led pásek ohebný</b>                               |
| Finish                        | <b>Jednořadý</b>                                      |
| Brand/Manufacturer            | <b>NBB</b>  |
| Colour                        | <b>RGB</b>  |
| Model                         | <b>Pásek</b>  |
| Dimmable                      | <b>Ano</b>  |
| Lamp voltage (V)              | <b>12 V</b>   |
| Self-adhesive                 | <b>Ano</b>  |
| Lamp type                     | <b>LED nevýměnné</b>                                  |
| Nominal voltage (V)           | <b>12 V</b>   |
| Degree of protection (IP)     | <b>IP65</b>   |
| Lowest bending radius         | <b>10 mm</b>  |
| Lamp power per meter          | <b>14,4 W</b>   |
| Length of particular segments | <b>50 mm</b>  |
| With connection set           | <b>Ne</b>   |
| With end piece                | <b>Ano</b>  |
| Název položky                 | <b>LED pásek 12V 60LED/m SMD5050 RGB IP65 14.4W/m</b> |

### Electrical characteristics

|                     |            |
|---------------------|------------|
| Voltage type        | <b>DC</b>  |
| Nominal current (A) | <b>6 A</b> |

### Working conditions

|                                       |                  |
|---------------------------------------|------------------|
| Dimmable range                        | <b>0 - 100 %</b> |
| Maximum permitted storage temperature | <b>70 °C</b>     |

|                                 |                         |
|---------------------------------|-------------------------|
| Burning position                | Libovolná               |
| Application                     | Dekoratívni osvětlování |
| Suitable for frequent switching | Ano                     |
| Ambient temperature             | -20/+35 °C              |
| Driver included                 | Ne                      |

#### Mounting methods/application

|                 |   |
|-----------------|---|
| Mounting method | Montáž na kovový chladič/nutné zajistit adekvátní chlazení! |
|-----------------|---|

#### Physical characteristics

|                           |                     |
|---------------------------|---------------------|
| Type of connector         | Vodiče s konektorem |
| Type of chip              | SMD 5050            |
| Weight gross              | 198 g               |
| Width                     | 10 mm               |
| Height                    | 2,5 mm              |
| Weight netto              | 184 g               |
| Length                    | 5000 mm             |
| Number of LEDs            | 300                 |
| Number of lamps per meter | 60                  |

#### EuP Parameters

|   |              |
|---|--------------|
| Luminescence Life maintenance factor                        | 70,0 %       |
| Factor of functional reliability (LSF) after nom. life      | 0,50 %       |
| Number of maximal switching cycles                          | >50000       |
| The rate of premature failures                              | 0,01 %       |
| Colour difference   | 85,0 %       |
| The light source is designed for outdoor and industrial use | Ano          |
| Rated service life  | 25000 h      |
| Energy consumption (AGGR)                                   | 72 kWh/1000h |

#### Lighting characteristics

|                  |              |
|------------------|--------------|
| Light Colour     | RGB          |
| Wavelength range | 400 - 750 nm |
| Radiation angle  | 120 °        |

#### Safety information

|                     |  |
|---------------------|--|
| Insulation class    | Třída III                                  |
| Safety instructions | <a href="http://www.nbb.cz">www.nbb.cz</a> |

#### Environmental characteristics

|                 |         |
|-----------------|---------|
| Mercury content | 0,00 mg |
|-----------------|---------|

#### Energetic characteristics

|                             |         |
|-----------------------------|---------|
| Rated efficiency after 100h | 99.99 % |
|-----------------------------|---------|

#### Exclusion of liability

Changes to data are subject to prior notice. NBB Bohemia s.r.o. accepts no responsibility for damages caused by inaccurate interpretation of the content on this site.

## Notice

Under the scope of Act 185/2001 Coll. as amended, this product is included in waste group 5 (light sources and luminaires). In view of the harmful effects of mercury on the environment and on human health, the creators of group 5 waste (consumers) are obliged to dispose of used light sources for recycling. Do not throw this product into mixed waste after use. Take it to the nearest store, collection yard, or other designated location for free recycling. You can also dispose of the used products for recycling in our sales outlets or in collection points of collective recycling systems or municipal collection yards. Ecological recycling of waste electrical and electronic equipment is ensured through the RETELA collective system ([www.retela.cz](http://www.retela.cz)).

## Warning

LED light sources must be operated so that they do not overheat. Overheating the light source may cause it to destroy or ignite. It is forbidden to connect the LED tapes wound onto the spool to voltage, there is a risk of fire! LED lamps without an integrated ballast may be operated on an electronic driver or other power supply that meets the supply conditions. It is necessary to observe the principles of power supply in the sense that some LED light sources are supplied with stabilized voltage and some stabilized current. Using an inappropriate power supply can damage the light source LED. NBB Bohemia is not responsible for defects in light sources caused by inappropriate power supply. In the case of LED strips with a higher power than 10W / m, it is not permissible to couple several strips in series. In this case, the LED strip at the connection point will become overheated and will be destroyed.

For powerful LED strips at higher power than 10W / m, adequate cooling is required. When designing cooling, the ambient temperatures must be taken into account. Powerful high-performance tapes with silicone or resin castings are not designed for continuous operation, as their cooling is problematic even when installed in aluminum bars that improve cooling. The company that manufactures powerful LED tapes has to design a cooling and operating time to make the tapes cool down. In the event that the tapes are destroyed by overheating, we will not be responsible for the damage caused.

## Notice

Single LED chip failure, luminous flux deviation +/- 10% as well as chromaticity deviation +/- 150K are in compliance with applicable standards and are not a reason for complaint.

## Popis

**NBB Bohemia s.r.o., Sídliště 693, 407 22 Benešov nad Ploučnicí**  
<https://www.nbb.cz/en/> | [hotmail@nbb.cz](mailto:hotmail@nbb.cz)

Copyright CE 2024 NBB Bohemia s.r.o Všechna práva vyhrazena.