


Product Data Sheet

LED pásek

LED Strip 12V 60LED/m
SMD5050 RGB IP20
7,2W/m multichip



Order number

903003075

Unit EAN13 code

8595209935274
General information

Model/Description	Led pásek ohebný
Finish	Jednořadý
Brand/Manufacturer	NBB
Colour	RGB
Model	Pásek
Dimmable	Ano
Lamp voltage (V)	12 V
Self-adhesive	Ano
Lamp type	LED nevýměnné
Nominal voltage (V)	12 V
Degree of protection (IP)	IP20
Lowest bending radius	10 mm
Lamp power per meter	7,2 W
Length of particular segments	100 mm
With connection set	Ne
With end piece	Ne
Název položky	LED pásek 12V 30LED/m SMD5050 RGB IP20 7.2W/m multichip

Electrical characteristics

Voltage type	DC
Nominal current (A)	3 A

Working conditions

Dimmable range	0 - 100 %
----------------	------------------

Maximum permitted storage temperature	70 °C
Burning position	Libovolná
Application	Dekorativní osvětlování
Suitable for frequent switching	Ano
Ambient temperature	-20/+35 °C
Driver included	Ne

Mounting methods/application

Mounting method	Montáž na kovový chladič/nutné zajistit adekvátní chlazení!
-----------------	---

Physical characteristics

Type of connector	Vodiče s volnými konci
Type of chip	SMD 5050
Weight gross	108 g
Width	10 mm
Height	2,5 mm
Weight netto	94 g
Length	5000 mm
Number of LEDs	150
Number of lamps per meter	30

EuP Parameters

Luminescence Life maintenance factor	70,0 %
Factor of functional reliability (LSF) after nom. life	0,50 %
Number of maximal switching cycles	>50000
The rate of premature failures	0,01 %
Colour difference	85,0 %
The light source is designed for outdoor and industrial use	Ne
Rated service life	25000 h
Energy consumption (AGGR)	36 kWh/1000h

Lighting characteristics

Light Colour	RGB
Wavelength range	400 - 750 nm
Radiation angle	120 °
Color temperature tolerance of +/-	10 %

Safety information

Insulation class	Třída III
Safety instructions	www.nbb.cz

Environmental characteristics

Mercury content	0,00 mg
-----------------	---------

Energetic characteristics

Rated efficiency after 100h	99.99 %
-----------------------------	---------

Exclusion of liability

Changes to data are subject to prior notice. NBB Bohemia s.r.o. accepts no responsibility for damages caused by inaccurate interpretation of the content on this site.

Notice

Under the scope of Act 185/2001 Coll. as amended, this product is included in waste group 5 (light sources and luminaires). In view of the harmful effects of mercury on the environment and on human health, the creators of group 5 waste (consumers) are obliged to dispose of used light sources for recycling. Do not throw this product into mixed waste after use. Take it to the nearest store, collection yard, or other designated location for free recycling. You can also dispose of the used products for recycling in our sales outlets or in collection points of collective recycling systems or municipal collection yards. Ecological recycling of waste electrical and electronic equipment is ensured through the RETELA collective system (www.retela.cz).

Warning

LED light sources must be operated so that they do not overheat. Overheating the light source may cause it to destroy or ignite. It is forbidden to connect the LED tapes wound onto the spool to voltage, there is a risk of fire! LED lamps without an integrated ballast may be operated on an electronic driver or other power supply that meets the supply conditions. It is necessary to observe the principles of power supply in the sense that some LED light sources are supplied with stabilized voltage and some stabilized current. Using an inappropriate power supply can damage the light source LED. NBB Bohemia is not responsible for defects in light sources caused by inappropriate power supply. In the case of LED strips with a higher power than 10W / m, it is not permissible to couple several strips in series. In this case, the LED strip at the connection point will become overheated and will be destroyed.

For powerful LED strips at higher power than 10W / m, adequate cooling is required. When designing cooling, the ambient temperatures must be taken into account. Powerful high-performance tapes with silicone or resin castings are not designed for continuous operation, as their cooling is problematic even when installed in aluminum bars that improve cooling. The company that manufactures powerful LED tapes has to design a cooling and operating time to make the tapes cool down. In the event that the tapes are destroyed by overheating, we will not be responsible for the damage caused.

Notice

Single LED chip failure, luminous flux deviation +/- 10% as well as chromaticity deviation +/- 150K are in compliance with applicable standards and are not a reason for complaint.

Popis

NBB Bohemia s.r.o., Sídliště 693, 407 22 Benešov nad Ploučnicí
<https://www.nbb.cz/en/> | hotmail@nbb.cz

Copyright CE 2024 NBB Bohemia s.r.o. Všechna práva vyhrazena.