



NBB Bohemia s.r.o.

Výroba a prodej osvětlovací techniky, Sídliště 693, 407 22 Benešov nad Ploučnicí



Product Data Sheet

LED žárovka

**LQ5 LED C35 240V 5W
E14 4000K NBB**

Order number

248000046

Unit EAN13 code

8595209942418



General information

Model/Description	Svíčková/Candle
Brand/Manufacturer	NBB
Lamp type	C37
Nominal service life (h)	25000 h
Colour	Bílá
Socket	E14
Dimmable	Ne
Energy efficiency class (canceled regulation!)	A+
Nominal voltage (V)	230 - 240 V
Degree of protection (IP)	IP20
Dimmable by conventional dimmers	Ne
Název položky	LQ5 LED C35 240V 5W E14 4000K NBB

Electrical characteristics

Nominal wattage	5 W
Rated power (W)	5,0 W
Operating voltage (V)	170 - 240 V
Type of Voltage	AC
Lowest permitted operating voltage (V)	170 V
Nominal current	43 mA
Lamp power	5 W
Voltage type	AC
With remote control	Ne
Nominal current (A)	0,043 A

Working conditions

Integrated driver	Ano
Operating frequency	50 - 60 Hz
Maximum permitted storage temperature	50 °C
Suitable for domestic use.	Ano
Application	Všeobecné osvětlování
Suitable for frequent switching	Ano
Ambient temperature	-10/+40 °C

Physical characteristics

Type of chip	2835
Dimensions (mm)	Ø37 x 102 mm
Packing method	1
Weight gross	41 g
Weight netto	32 g
Diameter	37 mm
Lamp shape	Svíčková
Length	102 mm
Type of glass/cover	Matný

EuP Parameters

Average Lifetime B50 (h)	25000 h
Luminescence Life maintenance factor	70,0 %
Factor of functional reliability (LSF) after nom. life	50,0 %
Time to 60 % luminous flux	0,3 s
Number of maximal switching cycles	25000
The rate of premature failures	<1 %
Colour difference	90 %
Rated service life	25000 h
Energy consumption (AGGR)	5 kWh/1000h
Turn-on time	<0,3 s
GLS replacement	37 W

Lighting characteristics

Color rendering	1B
Light Colour	chladná bílá
Dominant wavelength	451 nm
Luminous flux	420 lm
Colour temperature	4000 K
Colour rendering index CRI	80 Ra
Maximal intensity (Cd)	120 Cd
Colour of light	840
Colour controllable (RGB)	Ne
Beam angle Degrees (°)	120 °
Chromaticity coordinates x	0,320
Chromaticity coordinates y	0,350

Safety information

Safety instructions

www.nbb.cz

Environmental characteristics

Mercury content

0,00 mg

Energetic characteristics

Lamp Power factor (PF)

>0.5

Rated efficiency after 100h

99,99 %

Lamp efficacy

84,0 lm/W

Exclusion of liability

Changes to data are subject to prior notice. NBB Bohemia s.r.o. accepts no responsibility for damages caused by inaccurate interpretation of the content on this site.

Notice

Under the scope of Act 185/2001 Coll. as amended, this product is included in waste group 5 (light sources and luminaires). In view of the harmful effects of mercury on the environment and on human health, the creators of group 5 waste (consumers) are obliged to dispose of used light sources for recycling. Do not throw this product into mixed waste after use. Take it to the nearest store, collection yard, or other designated location for free recycling. You can also dispose of the used products for recycling in our sales outlets or in collection points of collective recycling systems or municipal collection yards. Ecological recycling of waste electrical and electronic equipment is ensured through the RETELA collective system (www.retela.cz).

Notice

Single LED chip failure, luminous flux deviation +/- 10% as well as chromaticity deviation +/- 150K are in compliance with applicable standards and are not a reason for complaint.

Popis

NBB Bohemia s.r.o., Sídliště 693, 407 22 Benešov nad Ploučnicí

<https://www.nbb.cz/en/> | hotmail@nbb.cz

Copyright CE 2024 NBB Bohemia s.r.o Všechna práva vyhrazena.