



Product Data Sheet

Reflektorové LED svítidlo ATEX

JAGUAR 100-277V 100W EX IP66

Order number

912601020

Unit EAN13 code

8595209951021


General information

Finish	ATEX
Suitable for suspended mounting	Ne
Lamp type	LED
Nominal voltage (V)	230 - 240 V
Degree of protection (IP)	IP66
Suitable for wall mounting	Ano
Suitable for traverse mounting	Ano
Suitable for pedestal/floor mounting	Ano
Suitable for ceiling mounting	Ano
Název položky	JAGUAR 100-277V 100W EX-BJG100 IP66

Electrical characteristics

Lamp power	100 W
Voltage type	AC
Nominal current (A)	0,3 A
System power	100 W

Working conditions

Type of control gear	Neuvedeno
Fire resistance "D"	Ano
Type of dimming	Nestmívatelné

Mounting methods/application

Mounting method	Přisazená
-----------------	------------------

Physical characteristics

Width	330 mm
Height	330 mm
Colour housing	Bez barvy
Adjustable	Ano
Length	150 mm
Material housing	Aluminium
Impact strength	IK10
For Ex-zone gas	2
Type of surface	Lesklý
For Ex-Zone dust	21,22,
Adjustability	Vertikálně

EuP Parameters

Rated service life	50000 h
--------------------	---------

Additional information

With lamp	Ano
-----------	-----

Lighting characteristics

Light Colour	chladná bílá
Colour temperature	4000 K
Colour rendering index CRI	70 Ra
Colour of light	740
Light sharing	Symetrické
Radiation angle	Široký úhel
Colour temperature	3600 - 4400 K
Effective luminous flux	10280 lm
Colour	Bílá

Safety information

Protection class	Ochranným vodičem
------------------	-------------------

Exclusion of liability

Changes to data are subject to prior notice. NBB Bohemia s.r.o. accepts no responsibility for damages caused by inaccurate interpretation of the content on this site.

Notice

Under the scope of Act 185/2001 Coll. as amended, this product is included in waste group 5 (light sources and luminaires). In view of the harmful effects of mercury on the environment and on human health, the creators of group 5 waste (consumers) are obliged to dispose of used light sources for recycling. Do not throw this product into mixed waste after use. Take it to the nearest store, collection yard, or other designated location for free recycling. You can also dispose of the used products for recycling in our sales outlets or in collection points of collective recycling systems or municipal collection yards. Ecological recycling of waste electrical and electronic equipment is ensured through the RETELA collective system (www.retela.cz).

Notice (LVD)

LED light sources ranks among electrotechnical products powered by mains 230-240V. For safety reasons, it is recommended that the assembly, connection or disassembly be carried out by a person with an appropriate electrotechnical qualification. When installing or disassembling, it is advisable to disconnect the power supply otherwise there may be a risk of electric shock. Only use the product in the luminaires designed for this type of light source. The manufacturer can not be held responsible for

damages resulting from inappropriate connection, connection to an unsuitable distribution system, or damages resulting from mechanical damage to the light source. Observe the operating values on the product. Do not expose the product to inappropriate weathering or high temperatures unless it is expressly stated that the product is intended to be operated under these conditions. When installing, wiring or disassembling, follow the generally accepted safety precautions.

Notice

Single LED chip failure, luminous flux deviation +/- 10% as well as chromaticity deviation +/- 150K are in compliance with applicable standards and are not a reason for complaint.

Popis

NBB Bohemia s.r.o., Sídliště 693, 407 22 Benešov nad Ploučnicí
<https://www.nbb.cz/en/> | hotmail@nbb.cz

Copyright CE 2024 NBB Bohemia s.r.o Všechna práva vyhrazena.