



NBB Bohemia s.r.o.

Výroba a prodej osvětlovací techniky, Sídliště 693, 407 22 Benešov nad Ploučnicí



Product Data Sheet

LED reflektor IP65

**ORION LED 230-240V
30W 6000K IP65 black**

Order number

253202020

Unit EAN13 code

8595209941428



General information

Model/Description	LED reflektor
Finish	Průmyslový
Brand/Manufacturer	NBB
Material	Aluminium
Nominal service life (h)	30000 h
Degree of protection (IP)	IP65
Dimmable	Ne
With light sensor	Ne
Suitable for suspended mounting	Ne
Lamp type	LED
Nominal voltage (V)	230 - 240 V
Degree of protection (IP)	IP65
Suitable for number of lamps	1
Suitable for wall mounting	Ano
Control gear included	Ano
Suitable for traverse mounting	Ano
Suitable for pedestal/floor mounting	Ano
Suitable for light-track mounting	Ne
Suitable for clamp-mounting	Ne
Suitable for ceiling mounting	Ano
Dimmable by conventional dimmers	Ne
Název položky	ORION LED 230-240V 30W 6000K IP65 black

Electrical characteristics

Nominal wattage	30 W
-----------------	-------------

Rated power (W)	30,8 W
Operating voltage (V)	110 - 240 V
Type of Voltage	AC
Lowest permitted operating voltage (V)	110 V
Voltage type	AC
Nominal current (A)	0,262 A
System power	30 W

Working conditions

Average lifetime of the ballast (h)	30000 h
Integrated driver	Ano
Light source is part of the fixture	Ano
Working temperature of the ballast body -Tc max	95 °C
Type of cooler	Aluminium
Installation height (m)	3 - 4 m
Application	Všeobecné osvětlování
Suitable for through-wiring	Ne
With movement sensor	Ne
Type of control gear	Elektronický nestmívatelný
Suitable for frequent switching	Ano
Ambient temperature	-30/+45 °C
Fire resistance "D"	Ano
Type of dimming	Nestmívatelné

Mounting methods/application

Mounting method	Přisazená
-----------------	-----------

Physical characteristics

Numbers of ballasts	1
Number of couplings	1
Type of chip	SMD2835
Dimensions (mm)	242 x 203 x 66 mm
Packing method	1 - 4
Weight gross	1921 g
Width	203 mm
Reflector	Matný
Colour housing	Černá
Weight netto	1772 g
Length	242 mm
Height/depth (mm)	66 mm
Material housing	Aluminium
Impact strength	IK10
Type of surface	Matný
Number of LEDs	60
Adjustability	Vertikálně

EuP Parameters

Average Lifetime B50 (h)	30000 h
--------------------------	---------

Luminescence Life maintenance factor	80,0 %
Factor of functional reliability (LSF) after nom. life	50,0 %
Time to 60 % luminous flux	0,3 s
Number of maximal switching cycles	>50000
The rate of premature failures	<0,1 %
Colour difference	90 %
Rated service life	30000 h
Energy consumption (AGGR)	33,0 kWh/1000h
Turn-on time	<0,3 s

Additional information

With lamp	Ano
-----------	-----

Lighting characteristics

Color rendering	2B
Light Colour	chladná denní
Wavelength range	380 - 780 nm
Dominant wavelength	760 nm
Luminous flux	3300 lm
Colour temperature	4200 K
Colour rendering index CRI	85 Ra
Colour of light	865
Light sharing	Symetrické
Radiation angle	Široký úhel
Colour temperature	6000 - 6500 K
Effective luminous flux	3300 lm
Colour	Bílá
Beam angle Degrees (°)	120 °
Chromaticity coordinates x	0,360
Chromaticity coordinates y	0,320

Safety information

Safety instructions	www.nbb.cz
Protection class	Ochranným vodičem

Environmental characteristics

Mercury content	0,00 mg
-----------------	---------

Energetic characteristics

Lamp Power factor (PF)	>0,9
Rated efficiency after 100h	99,99 %
Lamp efficacy	110 lm/W

Exclusion of liability

Changes to data are subject to prior notice. NBB Bohemia s.r.o. accepts no responsibility for damages caused by inaccurate interpretation of the content on this site.

Notice

Under the scope of Act 185/2001 Coll. as amended, this product is included in waste group 5 (light sources and luminaires). In view of the harmful effects of mercury on the environment and on human health, the creators of group 5 waste (consumers) are obliged to dispose of used light sources for recycling. Do not throw this product into mixed waste after use. Take it to the nearest store, collection yard, or other designated location for free recycling. You can also dispose of the used products for recycling in our sales outlets or in collection points of collective recycling systems or municipal collection yards. Ecological recycling of waste electrical and electronic equipment is ensured through the RETELA collective system (www.retela.cz).

Notice (LVD)

LED light sources ranks among electrotechnical products powered by mains 230-240V. For safety reasons, it is recommended that the assembly, connection or disassembly be carried out by a person with an appropriate electrotechnical qualification. When installing or disassembling, it is advisable to disconnect the power supply otherwise there may be a risk of electric shock. Only use the product in the luminaires designed for this type of light source. The manufacturer can not be held responsible for damages resulting from inappropriate connection, connection to an unsuitable distribution system, or damages resulting from mechanical damage to the light source. Observe the operating values on the product. Do not expose the product to inappropriate weathering or high temperatures unless it is expressly stated that the product is intended to be operated under these conditions. When installing, wiring or disassembling, follow the generally accepted safety precautions.

Notice

Single LED chip failure, luminous flux deviation +/- 10% as well as chromaticity deviation +/- 150K are in compliance with applicable standards and are not a reason for complaint.

Popis

NBB Bohemia s.r.o., Sídliště 693, 407 22 Benešov nad Ploučnicí
<https://www.nbb.cz/en/> | hotmail@nbb.cz

Copyright CE 2024 NBB Bohemia s.r.o. Všechna práva vyhrazena.