

Product Data Sheet



Led svítidlo do nižších výšek (low bay)



**SAULA LED SN 68W IP65
SN-EN1/4L/2000
440x430x75mm, NW-
4,5kg**

Order number
910465430

Unit EAN13 code
8595209947130

General information

Finish	SAULA LED SN 68W
Brand/Manufacturer	Ecolight
Nominal voltage (V)	230 - 240 V
Název položky	1 - 4
Počet LED kanálů	4

Electrical characteristics

Rated power (W)	68 W
Operating voltage (V)	230 - 240 V
Lamp power	68 W
Voltage type	AC

Working conditions

Average lifetime of the ballast (h)	50000 h
Driver included	Ano

Physical characteristics

Width	430 mm
Length	440 mm
Height/depth (mm)	75 mm

EuP Parameters

Average Lifetime B50 (h)	50000 h
Rated service life	50000 h

Lighting characteristics

Effective luminous flux

8155 lm

Exclusion of liability

Changes to data are subject to prior notice. NBB Bohemia s.r.o. accepts no responsibility for damages caused by inaccurate interpretation of the content on this site.

Notice

Under the scope of Act 185/2001 Coll. as amended, this product is included in waste group 5 (light sources and luminaires). In view of the harmful effects of mercury on the environment and on human health, the creators of group 5 waste (consumers) are obliged to dispose of used light sources for recycling. Do not throw this product into mixed waste after use. Take it to the nearest store, collection yard, or other designated location for free recycling. You can also dispose of the used products for recycling in our sales outlets or in collection points of collective recycling systems or municipal collection yards. Ecological recycling of waste electrical and electronic equipment is ensured through the RETELA collective system (www.retela.cz).

Notice (LVD)

LED light sources ranks among electrotechnical products powered by mains 230-240V. For safety reasons, it is recommended that the assembly, connection or disassembly be carried out by a person with an appropriate electrotechnical qualification. When installing or disassembling, it is advisable to disconnect the power supply otherwise there may be a risk of electric shock. Only use the product in the luminaires designed for this type of light source. The manufacturer can not be held responsible for damages resulting from inappropriate connection, connection to an unsuitable distribution system, or damages resulting from mechanical damage to the light source. Observe the operating values on the product. Do not expose the product to inappropriate weathering or high temperatures unless it is expressly stated that the product is intended to be operated under these conditions. When installing, wiring or disassembling, follow the generally accepted safety precautions.

Notice

Single LED chip failure, luminous flux deviation +/- 10% as well as chromaticity deviation +/- 150K are in compliance with applicable standards and are not a reason for complaint.

Popis

NBB Bohemia s.r.o., Sídliště 693, 407 22 Benešov nad Ploučnicí
<https://www.nbb.cz/en/> | hotmail@nbb.cz

Copyright CE 2024 NBB Bohemia s.r.o. Všechna práva vyhrazena.