



**NBB Bohemia s.r.o.**

Výroba a prodej osvětlovací techniky, Sídliště 693, 407 22 Benešov nad Ploučnicí

## Product Data Sheet

Kompaktní zářivka

**LD 11W/865 G23**  
**LIFETIME PLUS**



Order number

**221121000**

Unit EAN13 code

**8595209920294**

### General information

Model/Description	<b>Kompaktní zářivka</b>
Finish	<b>Single</b>
Brand/Manufacturer	<b>NBB</b>
Nominal service life (h)	<b>10000 h</b>
Colour	<b>Ostatní</b>
Socket	<b>G23 (2-pins)</b>
Dimmable	<b>Ne</b>
Energy efficiency class (canceled regulation!)	<b>A+</b>
Amalgam technology	<b>Ne</b>
Nominal voltage (V)	<b>91 V</b>
Dimmable by conventional dimmers	<b>Ne</b>
Název položky	<b>LD 11W/865 G23 LIFETIME PLUS</b>
Třída energetické účinnosti podle 2019/2015	<b>G</b>

### Electrical characteristics

Nominal wattage	<b>11 W</b>
Rated power (W)	<b>11,0 W</b>
Operating voltage (V)	<b>91 V</b>
Type of Voltage	<b>AC</b>
Direct connection to the mains	<b>Ne</b>
Lamp power	<b>11 W</b>
Ignitor	<b>SINGLE Glow starter</b>
Nominal current (A)	<b>0,155 A</b>
Total power (W) (light fitting)	<b>13,73 W</b>

### Working conditions

Operating frequency	50 - 60 Hz
Burning position	Libovolná
Application	Všeobecné osvětlování
Integrated starter	Ano
Suitable for electronic ballast	Ano
Ambient temperature	25 °C
Number of lighting tubes	2
Special application	Všeobecné osvětlování

### Physical characteristics

Dimensions (mm)	30 x 18 x 238 mm
Packing method	10 - 1
Weight gross	70 g
Width	30 mm
Depth (mm)	18 mm
Weight netto	50 g
Total lenght	238 mm
Diameter	30 mm
Length	238 mm

### EuP Parameters

Average Lifetime B50 (h)	10000 h
Luminescence Life maintenance factor	70,0 %
The rate of premature failures	< 1 %
Rated service life	10000 h
Energy consumption (AGGR)	11 kWh/1000h

### Lighting characteristics

Type of spectrum	Třípásmové
Color rendering	1B
Light Colour	chladná denní
Dominant wavelength	544 nm
Luminous flux	900 lm
Colour temperature	6500 K
Colour rendering index CRI	86 Ra
Colour of light	865
Colour of light acc. EN 12464-1	Cool >5300 K
Beam angle Degrees (°)	>120 °
Chromaticity coordinates x	0,320
Chromaticity coordinates y	0,328

### Safety information

Safety instructions	<a href="http://www.nbb.cz">www.nbb.cz</a>
---------------------	--------------------------------------------

### Environmental characteristics

Mercury content	3,50 mg
-----------------	---------

### Energetic characteristics

Rated efficiency after 100h	99,99 %
Lamp efficacy	81,81 lm/W

### Lamp survival factor (LSF)

LSF after 2.000 hrs	98,2 %
LSF after 4.000 hrs	96,3 %
LSF after 6.000 hrs	87,0 %
LSF after 8.000 hrs	50,0 %
LSF after 10.000 hrs	50,0 %

### Lamp lumen maintenance factor (LLMF)

LLMF after 2.000 hrs	85,0 %
LLMF after 4.000 hrs	78,0 %
LLMF after 6.000 hrs	75,0 %
LLMF after 8.000 hrs	73,0 %
LLMF after 10.000 hrs	70,0 %

### Exclusion of liability

Changes to data are subject to prior notice. NBB Bohemia s.r.o. accepts no responsibility for damages caused by inaccurate interpretation of the content on this site.

### Safety instructions

When replacing a fluorescent tube, first disconnect the luminaire from the electrical current supply. First remove the fluorescent lamp from the fixture and then install a new one. Take care to ensure that the product is not broken. Install the new fluorescent lamp by gently inserting it and turning it into the sides of the luminaire to any side. Only use the product in the luminaires designed for this type of light source. The manufacturer can not be held responsible for damages resulting from inappropriate connection, connection to an unsuitable distribution system, or damage resulting from the use of an unsuitable light source. Observe the operating values on the product. Do not expose the product to inappropriate weathering or high temperatures unless it is expressly stated that the product is intended to be operated under these conditions. When installing, wiring or disassembling, follow the generally accepted safety precautions. After installing a new fluorescent lamp, close the enclosure with original covers - to prevent possible electric shock. Only then connect the luminaire to the electrical circuit.

### Popis

Threephosphore 2-pin compact fluorescent lamps. Colour temperature 6500 K.

NBB Bohemia s.r.o., Sídliště 693, 407 22 Benešov nad Ploučnicí  
<https://www.nbb.cz/en/> | [hotmail@nbb.cz](mailto:hotmail@nbb.cz)

Copyright CE 2024 NBB Bohemia s.r.o Všechna práva vyhrazena.