



NBB Bohemia s.r.o.

Výroba a prodej osvětlovací techniky, Sídliště 693, 407 22 Benešov nad Ploučnicí

Product Data Sheet

Kompaktní zářivka LD REPTline®

PL-S 11W Reptile 12.0 UVB G23



Order number

221022000

Unit EAN13 code

8595209920973

General information

Model/Description	LD 11W/REPTILINE 12.0 DESERT
Finish	Single
Brand/Manufacturer	NBB
Nominal service life (h)	10000 h
Colour	Ostatní
Socket	G23 (2-pins)
Dimmable	Ne
Energy efficiency class (canceled regulation!)	A
Amalgam technology	Ne
Dimmable by conventional dimmers	Ne
Název položky	LD 11W/REPTILIGHT® 12.0 DESERT G23

Electrical characteristics

Nominal wattage	11 W
Rated power (W)	10,8 W
Operating voltage (V)	91 V
Type of Voltage	AC
Direct connection to the mains	Ne
Lamp power	11 W
Nominal current (A)	0,12 A

Working conditions

Burning position	Libovolná
Suitable for domestic use.	Ne
Application	Pro pouštění živočichy

Integrated starter	Ano
Suitable for electronic ballast	Ano
Ambient temperature	25 °C
Number of lighting tubes	1
Special application	Terária

Physical characteristics

Dimensions (mm)	30 x 18 x 238 mm
Packing method	50 - 1
Weight gross	70 g
Weight netto	50 g
Total lenght	238 mm
Diameter	30 mm

EuP Parameters

Average Lifetime B50 (h)	10000 h
Luminescence Life maintenance factor	70,0 %
Number of maximal switching cycles	>20.000
The rate of premature failures	<1 %
Rated service life	10000 h
Energy consumption (AGGR)	15 kWh/1000h

Lighting characteristics

Type of spectrum	Plné spektrum
Color rendering	1A
Light Colour	natural daylight
Dominant wavelength	433 nm
Luminous flux	580 lm
Colour temperature	14000 K
Colour rendering index CRI	90 Ra
Type of UV radiation	UVA+UVB
Chromaticity coordinates x	0.271
Chromaticity coordinates y	0.260

Safety information

Safety instructions	www.nbb.cz
---------------------	--------------------------------------------

Environmental characteristics

Mercury content	3,5 mg
-----------------	--------

Energetic characteristics

Rated efficiency after 100h	99,99 %
Lamp efficacy	57,1 lm/W

Lamp survival factor (LSF)

LSF after 2.000 hrs	98,2 %
LSF after 4.000 hrs	96,3 %

LSF after 6.000 hrs	87,0 %
LSF after 8.000 hrs	50,0 %
LSF after 10.000 hrs	50,0 %

Lamp lumen maintenance factor (LLMF)

LLMF after 2.000 hrs	85,0 %
LLMF after 4.000 hrs	78,0 %
LLMF after 6.000 hrs	75,0 %
LLMF after 8.000 hrs	73,0 %
LLMF after 10.000 hrs	70,0 %

Exclusion of liability

Changes to data are subject to prior notice. NBB Bohemia s.r.o. accepts no responsibility for damages caused by inaccurate interpretation of the content on this site.

Safety instructions

When replacing a fluorescent tube, first disconnect the luminaire from the electrical current supply. First remove the fluorescent lamp from the fixture and then install a new one. Take care to ensure that the product is not broken. Install the new fluorescent lamp by gently inserting it and turning it into the sides of the luminaire to any side. Only use the product in the luminaires designed for this type of light source. The manufacturer can not be held responsible for damages resulting from inappropriate connection, connection to an unsuitable distribution system, or damage resulting from the use of an unsuitable light source. Observe the operating values on the product. Do not expose the product to inappropriate weathering or high temperatures unless it is expressly stated that the product is intended to be operated under these conditions. When installing, wiring or disassembling, follow the generally accepted safety precautions. After installing a new fluorescent lamp, close the enclosure with original covers - to prevent possible electric shock. Only then connect the luminaire to the electrical circuit.

Popis

Fluorescent lamp with special daylight spectrum for desert animals. (12% UVB)

NBB Bohemia s.r.o., Sídliště 693, 407 22 Benešov nad Ploučnicí
<https://www.nbb.cz/en/> | hotmail@nbb.cz

Copyright © 2024 NBB Bohemia s.r.o. Všechna práva vyhrazena.