



NBB Bohemia s.r.o.

Výroba a prodej osvětlovací techniky, Sídliště 693, 407 22 Benešov nad Ploučnicí



Product Data Sheet

Kompaktní zářivka

**Energy sav.lamp T2 Full
Spiral 240V 7W E14**



Order number

235430000

Unit EAN13 code

8595209923073

General information

Model/Description	Kompaktní zářivka amalgámová
Finish	Full spiral T2
Brand/Manufacturer	NBB
Nominal service life (h)	10000 h
Dimmable	Ne
Energy efficiency class (canceled regulation!)	A
Nominal voltage (V)	220-240 V
Dimmable by conventional dimmers	Ne
Název položky	GL-S 7W/840 SUPER E14 NBB

Electrical characteristics

Nominal wattage	7 W
Rated power (W)	7,1 W
Operating voltage (V)	220-240 V
Type of Voltage	AC
Direct connection to the mains	Ano
Nominal current (A)	0,059 A

Working conditions

Type of start	Warm
Output frequency of ballast (driver)	>40 kHz kHz
Operating frequency	50 - 60 Hz
Burning position	Universal
Suitable for domestic use.	Ano
Application	Všeobecné osvětlování/General lighting

Type of control gear	Elektronický
Ambient temperature	40 °C

Physical characteristics

Dimensions (mm)	Ø45 x 81 mm
Packing method	10 - 1
Weight gross	62 g g
Weight netto	38 g g

EuP Parameters

Average Lifetime B50 (h)	10000 h
Luminescence Life maintenance factor	50,0 % %
Time to 60 % luminous flux	<45 s s
Number of maximal switching cycles	>10.000
The rate of premature failures	≤ 2,0 % %
Rated service life	10000 h
Energy consumption (AGGR)	7,1 kWh/1000h
Turn-on time	<1 s s
GLS replacement	17,4 W W

Additional information

Note	GreenProduct®
------	---------------

Lighting characteristics

Type of spectrum	Třípásmové
Color rendering	1B
Light Colour	coolwhite/chladná bílá
Dominant wavelength	612 nm
Luminous flux	400 lm
Colour temperature	4000 K
Colour rendering index CRI	>80 Ra8 Ra
Colour of light	840
Chromaticity coordinates x	0,382
Chromaticity coordinates y	0,362

Radiation in the UV range

UVA a UVB radiation	≤ 2,0 mW/klm mW/klm
UVC radiation	≤ 0,01 mW/klm mW/klm

Safety information

Safety instructions	www.nbb.cz
---------------------	--

Environmental characteristics

Mercury content	2,00 mg
-----------------	---------

Energetic characteristics

Lamp Power factor (PF)	0,53
------------------------	------

Rated efficiency after 100h	99,99 % %
-----------------------------	-----------

Lamp efficacy	42,85 lm/W
---------------	------------

Lamp lumen maintenance factor (LLMF)

LLMF after 2.000 hrs	>90,0 % %
----------------------	-----------

Exclusion of liability

Changes to data are subject to prior notice. NBB Bohemia s.r.o. accepts no responsibility for damages caused by inaccurate interpretation of the content on this site.

Popis

Amalgam technology, 10.000 switch cycles, life10.000 h. CCT 4000 K, Ra 80+

NBB Bohemia s.r.o., Sídliště 693, 407 22 Benešov nad Ploučnicí

<https://www.nbb.cz/en/> | hotmail@nbb.cz

Copyright CE 2024 NBB Bohemia s.r.o Všechna práva vyhrazena.