



Product Data Sheet

Kompaktní zářivka

**GL-S 11W/865 SUPER E14
NBB**


Order number

235444000

Unit EAN13 code

8595209913968

General information

Model/Description	Kompaktní zářivka amalgámová
Finish	Full spiral T2
Brand/Manufacturer	NBB
Nominal service life (h)	10000 h
Dimmable	Ne
Energy efficiency class (canceled regulation!)	A
Nominal voltage (V)	230-240 V
Dimmable by conventional dimmers	Ne
Název položky	GL-S 11W/865 SUPER E14 NBB

Electrical characteristics

Nominal wattage	11 W
Rated power (W)	11,0 W
Operating voltage (V)	220-240 V V
Type of Voltage	AC
Lamp operating current	85 mA A
Direct connection to the mains	Ano
Nominal current (A)	85 A

Working conditions

Type of start	Warm
Output frequency of ballast (driver)	>40 kHz kHz
Operating frequency	50 - 60 Hz
Burning position	Universal
Suitable for domestic use.	Ano

Application	Pro všeobecné osvětlování
Type of control gear	Elektronický
Ambient temperature	40 °C
Physical characteristics	
Dimensions (mm)	Ø45 x 91 mm
Packing method	10 - 1
Weight gross	70 g g
Weight netto	46 g g
EuP Parameters	
Average Lifetime B50 (h)	10000 h
Luminescence Life maintenance factor	50,0 % %
Time to 60 % luminous flux	<60 s s
Number of maximal switching cycles	>10.000
The rate of premature failures	<1 % %
Rated service life	10000 h
Energy consumption (AGGR)	11 kWh/1000h
Turn-on time	<1 s s
GLS replacement	50,5 W W
Additional information	
Note	GreenProduct®
Lighting characteristics	
Type of spectrum	Třípásmové
Color rendering	1B
Light Colour	cool daylight/chladná denní
Dominant wavelength	612 nm
Luminous flux	594 lm
Colour temperature	6500 K
Colour rendering index CRI	>80 Ra8 Ra
Colour of light	865
Chromaticity coordinates x	0,340
Chromaticity coordinates y	0,323
Radiation in the UV range	
UVA a UVB radiation	<2,0 mW/klm mW/klm
UVC radiation	<0,01 mW/klm mW/klm
Safety information	
Safety instructions	www.nbb.cz
Environmental characteristics	
Maximum mercury content (mg)	>2,00 mg

Energetic characteristics

Lamp Power factor (PF)	>0,5 <25W, 0,9>25W
Rated efficiency after 100h	99,99 % %
Lamp efficacy	54,00 lm/W

Lamp lumen maintenance factor (LLMF)

LLMF after 2.000 hrs	>90,0 % %
----------------------	-----------

Exclusion of liability

Changes to data are subject to prior notice. NBB Bohemia s.r.o. accepts no responsibility for damages caused by inaccurate interpretation of the content on this site.

Popis

Amalgam technology, 10.000 switch cycles, life10.000 h. CCT 6500 K, Ra 80+

NBB Bohemia s.r.o., Sídliště 693, 407 22 Benešov nad Ploučnicí
<https://www.nbb.cz/en/> | hotmail@nbb.cz

Copyright CE 2024 NBB Bohemia s.r.o Všechna práva vyhrazena.