



## Product Data Sheet

Metal-halogenidová výbojka

**JCL-TC 35W/942 UVS**  
**G8,5 JENBO**

Order number

**739102000**

Unit EAN13 code

**8595209911438**


### General information

Model/Description	<b>Vysokotlaká výbojka</b>
Finish	<b>Keramická</b>
Brand/Manufacturer	<b>JENBO</b>
Bulb finish	<b>clear</b>
Nominal service life (h)	<b>15000 h</b>
Model	<b>Čirá</b>
Socket	<b>G8.5</b>
Dimmable	<b>Ano</b>
Energy efficiency class (canceled regulation!)	<b>A</b>
Lamp voltage	<b>84 - 90 V</b>
Dimmable by conventional dimmers	<b>Ne</b>
Název položky	<b>JCL-TC 35W/942 UVS G8,5 JENBO</b>

### Electrical characteristics

Nominal wattage	<b>35 W</b>
Rated power (W)	<b>37 W</b>
Compatible ballast	<b>JENBO JB35</b>
Operating voltage (V)	<b>84 - 90 V</b>
Type of Voltage	<b>AC</b>
Pulse height	<b>5 kV</b>
Lamp operating current	<b>0,5 A A</b>
Lamp power	<b>35 W</b>
Nominal current (A)	<b>0,5 A</b>
Total power (W) (light fitting)	<b>35 W</b>

### Working conditions

Ambiente temperature for max. luminous flux	max 180s/25°C °C
Hot restart	Ne
Bulb temperature (max.)	500 °C
Cap temperature (max.)	300 °C
Burning position	Libovolná
Application	Pro uzavřená výbojková svítidla
Burning position	Libovolná
External ignitor required	Ano
External ballast required	Ano
Material discharge tube	Keramický
Closed luminaire required	Ano

### Physical characteristics

Dimensions (mm)	15 x 85 mm
Packing method	10 - 1
Weight gross	14 g
Weight netto	8 g
Total lenght	85 mm
Diameter	15 mm
Lamp shape	Jednopaticová válcová
Coated	Ne

### EuP Parameters

Average Lifetime B50 (h)	15000 h
The rate of premature failures	<1 %
Rated service life	15000 h
Energy consumption (AGGR)	40,7 kWh/1000h
Turn-on time	max 30 s
Φ 90°	3570 lm

### Lighting characteristics

Lenght of arc	4,8 mm
Color rendering	1A
Light Colour	neutrální bílá
Luminous flux	3570 lm
Colour temperature	4200 K
Colour rendering index CRI	91 Ra
Sun tanning lamp	Ne
Colour of light	942
Colour of light acc. EN 12464-1	Neutral 3300-5300 K
Chromaticity coordinates x	0,350
Chromaticity coordinates y	0,330

### Radiation in the UV range

UV protect	Ano
------------	-----

## Safety information

Safety instructions	<a href="http://www.nbb.cz">www.nbb.cz</a>
---------------------	--------------------------------------------

## Environmental characteristics

Maximum mercury content (mg)	max 4,00 mg
------------------------------	-------------

## Energetic characteristics

Rated efficiency after 100h	99,8 %
Lamp efficacy	102 lm/W

## Lamp survival factor (LSF)

LSF after 2.000 hrs	99,5 %
LSF after 6.000 hrs	95 %
LSF after 8.000 hrs	90 %
LSF after 9.000 hrs	80 %
LSF after 10.000 hrs	60 %
LSF after 12.000 hrs	50 %

## Lamp lumen maintenance factor (LLMF)

LLMF after 2.000 hrs	80 %
LLMF after 5.000 hrs	60 %
LLMF after 10.000 hrs	50 %
LLMF after 12.000 hrs	40 %

## Exclusion of liability

Changes to data are subject to prior notice. NBB Bohemia s.r.o. accepts no responsibility for damages caused by inaccurate interpretation of the content on this site.

## Popis

Ceramic metal-halide lamps, longlife 15.000 h, Ra 90+, UV-stop, 3.100 lm, monolith burner

**NBB Bohemia s.r.o., Sídliště 693, 407 22 Benešov nad Ploučnicí**  
<https://www.nbb.cz/en/> | [hotmail@nbb.cz](mailto:hotmail@nbb.cz)

Copyright CE 2024 NBB Bohemia s.r.o Všechna práva vyhrazena.