



Product Data Sheet

Metal-halogenidová výbojka

JLS-T 150W/830 UVS
CERA® G12 MINI

Order number

741031010

Unit EAN13 code

8595209921468


General information

Model/Description	Vysokotlaká výbojka
Finish	Křemíková/Quartz
Brand/Manufacturer	NBB
Bulb finish	clear
Material	Hard Glass
Nominal service life (h)	10000 h
Model	Čirá
Socket	G12
Dimmable	Ano
Energy efficiency class (canceled regulation!)	A
Lamp voltage	90 - 95 V
Dimmable by conventional dimmers	Ne
Název položky	JLS-T 150W/830 UVS CERA® G12 MINI

Electrical characteristics

Nominal wattage	150 W
Rated power (W)	150,0 W
Compatible ballast	1,8-2,0 A
Operating voltage (V)	95 V
Type of Voltage	AC
Pulse height	5 kV
Lamp operating current	1,80 A
Direct connection to the mains	Ne
Lamp power	150 W
Nominal current (A)	1,80 A

Working conditions

Ambiente temperature for max. luminous flux	max 180s/25°C °C
Hot restart	Ne
Bulb temperature (max.)	500 °C
Cap temperature (max.)	300 °C
Burning position	Libovolná
Application	Pro uzavřená svítidla
Burning position	Libovolná
External ignitor required	Ano
External ballast required	Ano
Material discharge tube	Quartz
Closed luminaire required	Ano

Mounting methods/application

Mounting method	Uzavřená svítidla
-----------------	-------------------

Physical characteristics

Dimensions (mm)	Ø25 x 84 mm
Packing method	10 - 1
Weight gross	38 g
Weight netto	30 g
Total lenght	84 mm
Diameter	25 mm
Lamp shape	Jednopaticová válcová
Coated	Ne

EuP Parameters

Average Lifetime B50 (h)	10000 h
The rate of premature failures	<1 %
Rated service life	10000 h
Energy consumption (AGGR)	165 kWh/1000h
Turn-on time	max 30 s

Lighting characteristics

Lenght of arc	4,8 mm
Color rendering	1B
Light Colour	teplá bílá
Dominant wavelength	412 nm
Luminous flux	13000 lm
Colour temperature	3000 K
Colour rendering index CRI	85 Ra
Sun tanning lamp	Ne
Colour of light	830
Colour of light acc. EN 12464-1	Warm <3300 K
Chromaticity coordinates x	0,443
Chromaticity coordinates y	0,409

Radiation in the UV range

UV protect	Ano
------------	-----

Safety information

Safety instructions	www.nbb.cz
---------------------	--

Environmental characteristics

Maximum mercury content (mg)	max 4,00 mg
------------------------------	-------------

Energetic characteristics

Rated efficiency after 100h	99,8 %
Lamp efficacy	86,66 lm/W

Lamp survival factor (LSF)

LSF after 2.000 hrs	90,0 %
LSF after 4.000 hrs	75,0 %
LSF after 6.000 hrs	50,0 %
LSF after 8.000 hrs	90 %
LSF after 9.000 hrs	80 %
LSF after 10.000 hrs	50 %
LSF after 12.000 hrs	50 %

Lamp lumen maintenance factor (LLMF)

LLMF after 2.000 hrs	80,0 %
LLMF after 4.000 hrs	60,0 %
LLMF after 5.000 hrs	60 %
LLMF after 6.000 hrs	60,0 %
LLMF after 10.000 hrs	50 %
LLMF after 12.000 hrs	40 %

Exclusion of liability

Changes to data are subject to prior notice. NBB Bohemia s.r.o. accepts no responsibility for damages caused by inaccurate interpretation of the content on this site.

Popis

Ceramic metal-halide lamps MINI, 10.000 h, Ra 80+, UV-stop, 13.000 lm, 3000 K, only for enclosed fixture

NBB Bohemia s.r.o., Sídliště 693, 407 22 Benešov nad Ploučnicí
<https://www.nbb.cz/en/> | hotmail@nbb.cz

Copyright CE 2024 NBB Bohemia s.r.o. Všechna práva vyhrazena.