



Product Data Sheet

Stage lamps

NSK 150/2 JENBO®
GY9,5

Order number

800015000

Unit EAN13 code

8595209939647



General information

Specifications	150 - 2
Model/Description	Jednopicová projekční výbojka
Brand/Manufacturer	JENBO
Nominal service life (h)	3000 h
Socket	GY9.5
Dimmable	Ne
Length of arc	5,5 mm
Nominal voltage (V)	90 - 95 V
Lamp voltage	90 - 95 V
Název položky	150 - 2

Electrical characteristics

Nominal wattage	150 W
Rated power (W)	150,0 W
Operating voltage (V)	90 - 95 V
Type of Voltage	AC
Direct connection to the mains	Ne
Lamp power	150 W
Technology	Metal-halogen
Nominal current (A)	1,80 A

Working conditions

Hot restart	Ne
Burning position	Libovolná
Application	Studiové osvětlování a projekční technika

Burning position	Libovolná
------------------	-----------

Physical characteristics

Light centre length (mm)	56,0 mm
Dimensions (mm)	Ø20 x 105 mm
Packing method	1
Weight gross	20 g
Light centre height (mm)	56,0 mm
Weight netto	15 g
Total lenght	105 mm
Diameter	20 mm
Number of Burners	1

EuP Parameters

Average Lifetime B50 (h)	3000 h
The rate of premature failures	<1 %
Rated service life	3000 h
Energy consumption (AGGR)	165 kWh/1000h
Turn-on time	<10 s

Lighting characteristics

Lenght of arc	5,5 mm
Luminous flux	12000 lm
Colour temperature	7000 K

Radiation in the UV range

UV-protection	Ne
---------------	----

Safety information

Safety instructions	www.nbb.cz
---------------------	--

Energetic characteristics

Lamp efficacy	80 lm/W
---------------	---------

Exclusion of liability

Changes to data are subject to prior notice. NBB Bohemia s.r.o. accepts no responsibility for damages caused by inaccurate interpretation of the content on this site.

Popis

Single ended ceramic discharge stage lamp. Direct replacement HSD 150/70

NBB Bohemia s.r.o., Sídliště 693, 407 22 Benešov nad Ploučnicí
<https://www.nbb.cz/en/> | hotmail@nbb.cz

Copyright CE 2024 NBB Bohemia s.r.o Všechna práva vyhrazena.