



Product Data Sheet

Hot Restart

NSK400/HR JENBO


Order number

800050000

Unit EAN13 code

8595209939715

General information

Specifications	NSK 400/HR
Model/Description	Jednopicová projekční výbojka
Brand/Manufacturer	JENBO
Lamp type	Metal halide/Metalhalogenidová
Nominal service life (h)	750 h
Socket	GZ9.5
Dimmable	Ne
Length of arc	6,0 mm
Lamp voltage	70 - 80 V
Dimmable by conventional dimmers	Ne
Název položky	NSK 400/HR JENBO® (Hot Reset) GZ9,5

Electrical characteristics

Nominal wattage	400 W
Rated power (W)	400,0 W
Operating voltage (V)	70 - 80 V
Type of Voltage	AC
Lamp power	400 W
Technology	Metal-halogen
Nominal current (A)	6,9 A

Working conditions

Hot restart	Ano
Burning position	Libovolná
Application	Studiové osvětlování a projekční technika

Burning position **Libovolná**

Mounting methods/application

Mounting method **Uzavřená svítidla**

Physical characteristics

Light centre length (mm)	62 mm
Dimensions (mm)	ø22 x 112 mm
Packing method	1
Weight gross	64 g
Light centre height (mm)	62,0 mm
Weight netto	34 g
Total lenght	112 mm
Diameter	22 mm
Number of Burners	1

EuP Parameters

Average Lifetime B50 (h)	750 h
The rate of premature failures	<1 %
Rated service life	750 h
Energy consumption (AGGR)	440 kWh/1000h

Lighting characteristics

Lenght of arc	6,0 mm
Luminous flux	32000 lm
Colour temperature	6000 K
Colour rendering index CRI	85 Ra
Colour of light	860

Safety information

Safety instructions **www.nbb.cz**

Energetic characteristics

Lamp efficacy **80,0 lm/W**

Exclusion of liability

Changes to data are subject to prior notice. NBB Bohemia s.r.o. accepts no responsibility for damages caused by inaccurate interpretation of the content on this site.

Popis

Single ended ceramic discharge stage lamp. Direct replacement HSR 400W/72, MSR 400W/2, NSD400/2.

NBB Bohemia s.r.o., Sídliště 693, 407 22 Benešov nad Ploučnicí
<https://www.nbb.cz/en/> | hotmail@nbb.cz

Copyright CE 2024 NBB Bohemia s.r.o Všechna práva vyhrazena.