



Product Data Sheet

Short Arc

NSK2500 JENBO

Order number

800120000

Unit EAN13 code

8595209939890


General information

Specifications	NSK 2500
Model/Description	Jednopicová projekční výbojka
Brand/Manufacturer	JENBO
Lamp type	Metal halide/Metalhalogenidová
Nominal service life (h)	500 h
Socket	G38
Dimmable	Ne
Length of arc	14 mm
Lamp voltage	115 - 120 V
Název položky	NSK 2500 JENBO® G38

Electrical characteristics

Nominal wattage	2500 W
Rated power (W)	2500,0 W
Operating voltage (V)	115 - 120 V
Type of Voltage	AC
Lamp power	2500 W
Technology	Metal-halogen
Nominal current (A)	25,6 A

Working conditions

Hot restart	Ano
Burning position	Libovolná
Application	Projekční technika
Burning position	Libovolná

Mounting methods/application

Mounting method	Uzavřená svítidla
-----------------	-------------------

Physical characteristics

Light centre length (mm)	127 mm
Dimensions (mm)	Ø60 x 225 mm
Packing method	1
Weight gross	222 g
Light centre height (mm)	127 mm
Weight netto	164 g
Total length	225 mm
Diameter	60 mm
Number of Burners	1

EuP Parameters

Average Lifetime B50 (h)	500 h
The rate of premature failures	<1 %
Rated service life	500 h
Energy consumption (AGGR)	2750 kWh/1000h

Lighting characteristics

Length of arc	14,0 mm
Luminous flux	240000 lm
Colour temperature	6000 K
Colour rendering index CRI	96 Ra
Colour of light	960

Safety information

Safety instructions	www.nbb.cz
---------------------	--

Energetic characteristics

Lamp efficacy	95,0 lm/W
---------------	-----------

Exclusion of liability

Changes to data are subject to prior notice. NBB Bohemia s.r.o. accepts no responsibility for damages caused by inaccurate interpretation of the content on this site.

Popis

Single ended ceramic discharge stage lamp. Direct replacement HSR 2500W/SE,MSR 2500W/HR, NSD2500.

NBB Bohemia s.r.o., Sídliště 693, 407 22 Benešov nad Ploučnicí
<https://www.nbb.cz/en/> | hotmail@nbb.cz

Copyright CE 2024 NBB Bohemia s.r.o Všechna práva vyhrazena.