



Product Data Sheet

reflektorová projekční výbojka

MHK250/R JENBO



Order number

800215000

Unit EAN13 code

8595209939920

General information

Specifications	MHK 250/R
Model/Description	Vysokotlaká projekční výbojka
Finish	Reflektorová
Brand/Manufacturer	JENBO
Lamp type	Metal halide/Metalhalogenidová
Nominal service life (h)	1000 h
Socket	Ostatní
Dimmable	Ne
Lamp voltage	90 - 100 V
Dimmable by conventional dimmers	Ne
Název položky	MHK 250/R JENBO® cable

Electrical characteristics

Nominal wattage	250 W
Rated power (W)	250,0 W
Compatible ballast	3,5
Operating voltage (V)	85 - 90 V
Type of Voltage	AC
Lamp power	250 W
Technology	Metal-halogen
Nominal current (A)	3,5 A

Working conditions

Hot restart	Ne
Burning position	Libovolná

Application	Projekční technika
-------------	--------------------

Mounting methods/application

Mounting method	Uzavřená svítidla
-----------------	-------------------

Physical characteristics

Dimensions (mm)	Ø27 x 75 x 80 mm
Packing method	1
Weight gross	0,112 g
Weight netto	80 g
Total lenght	72 mm
Diameter	70 mm
Lamp shape	Reflektorová s jednostrannou paticí
Number of Burners	1
Reflector diameter	50 mm

EuP Parameters

Average Lifetime B50 (h)	500 h
The rate of premature failures	<1 %
Rated service life	1000 h
Energy consumption (AGGR)	275 kWh/1000h

Lighting characteristics

Lenght of arc	3,0 mm
Luminous flux	18250 lm
Colour temperature	7000 K
Colour of light	JB7000K

Safety information

Safety instructions	www.nbb.cz
---------------------	--

Energetic characteristics

Lamp efficacy	73,0 lm/W
---------------	-----------

Exclusion of liability

Changes to data are subject to prior notice. NBB Bohemia s.r.o. accepts no responsibility for damages caused by inaccurate interpretation of the content on this site.

Popis

Stage metal-halide reflector lamps.

NBB Bohemia s.r.o., Sídliště 693, 407 22 Benešov nad Ploučnicí
<https://www.nbb.cz/en/> | hotmail@nbb.cz

Copyright CE 2024 NBB Bohemia s.r.o Všechna práva vyhrazena.