



NBB Bohemia s.r.o.

Výroba a prodej osvětlovací techniky, Sídliště 693, 407 22 Benešov nad Ploučnicí



Product Data Sheet

Double-End

MHK400/2 D3 JENBO



Order number

800230000

Unit EAN13 code

8595209939951

General information

Specifications	400 - 2
Model/Description	Vysokotlaká projekční výbojka
Finish	S oboustrannou paticí
Brand/Manufacturer	JENBO
Nominal service life (h)	750 h
Socket	SFC10-4
Dimmable	Ne
Length of arc	3,0 mm
Lamp voltage	50 - 55 V
Název položky	400 - 2

Electrical characteristics

Nominal wattage	400 W
Rated power (W)	400,0 W
Operating voltage (V)	50 - 55 V
Type of Voltage	AC
Lamp power	400 W
Technology	Metal-halogen
Nominal current (A)	8,50 A

Working conditions

Hot restart	Ano
Burning position	Libovolná
Application	Studiové osvětlování a projekční technika
Burning position	Libovolná

Mounting methods/application

Mounting method	Uzavřená svítidla
-----------------	-------------------

Physical characteristics

Dimensions (mm)	Ø17 x 136 mm
Packing method	1
Weight gross	86 g
Weight netto	30 g
Total length	136 mm
Diameter	17 mm
Number of Burners	1

EuP Parameters

Average Lifetime B50 (h)	750 h
The rate of premature failures	<1 %
Rated service life	750 h
Energy consumption (AGGR)	440 kWh/1000h

Lighting characteristics

Length of arc	3 mm
Luminous flux	26000 lm
Colour temperature	7500 K
Colour rendering index CRI	80 Ra
Colour of light	875

Safety information

Safety instructions	www.nbb.cz
---------------------	--

Energetic characteristics

Lamp efficacy	65,0 lm/W
---------------	-----------

Exclusion of liability

Changes to data are subject to prior notice. NBB Bohemia s.r.o. accepts no responsibility for damages caused by inaccurate interpretation of the content on this site.

Popis

Stage metal-halide lamps. Direct replacement HTI 400W/D3/75, MSR 400/2 SA/DE, HQM400.

NBB Bohemia s.r.o., Sídliště 693, 407 22 Benešov nad Ploučnicí
<https://www.nbb.cz/en/> | hotmail@nbb.cz

Copyright CE 2024 NBB Bohemia s.r.o Všechna práva vyhrazena.