



NBB Bohemia s.r.o.

Výroba a prodej osvětlovací techniky, Sídliště 693, 407 22 Benešov nad Ploučnicí



Product Data Sheet

Short Src and High Colour

MHK575/2/D4 JENBO



Order number

800250000

Unit EAN13 code

8595209939999

General information

| | |
|--------------------------|---------------------------------------|
| Specifications | MHK 575/D4 |
| Model/Description | Vysokotlaká projekční výbojka |
| Finish | S oboustrannou paticí |
| Brand/Manufacturer | JENBO |
| Lamp type | Metal halide/Metalhalogenidová |
| Nominal service life (h) | 750 h |
| Socket | SFC10-4 |
| Dimmable | Ne |
| Length of arc | 4,0 mm |
| Lamp voltage | 65 - 70 V |
| Název položky | 575 - 2 |

Electrical characteristics

| | |
|-----------------------|----------------------|
| Nominal wattage | 575 W |
| Rated power (W) | 575,0 W |
| Operating voltage (V) | 65 - 70 V |
| Type of Voltage | AC |
| Lamp power | 575 W |
| Technology | Metal-halogen |
| Nominal current (A) | 8,3 A |

Working conditions

| | |
|------------------|--------------------------------------------------|
| Hot restart | Ano |
| Burning position | Libovolná |
| Application | Studiové osvětlování a projekční technika |

| | |
|------------------|-----------|
| Burning position | Libovolná |
|------------------|-----------|

Mounting methods/application

| | |
|-----------------|-------------------|
| Mounting method | Uzavřená svítidla |
|-----------------|-------------------|

Physical characteristics

| | |
|-------------------|--------------|
| Dimensions (mm) | Ø20 x 136 mm |
| Packing method | 1 |
| Weight gross | 88 g |
| Weight netto | 32 g |
| Total lenght | 136 mm |
| Diameter | 20 mm |
| Number of Burners | 1 |

EuP Parameters

| | |
|--------------------------------|-----------------|
| Average Lifetime B50 (h) | 750 h |
| The rate of premature failures | <1 % |
| Rated service life | 750 h |
| Energy consumption (AGGR) | 632,5 kWh/1000h |

Lighting characteristics

| | |
|----------------------------|----------|
| Lenght of arc | 4,0 mm |
| Luminous flux | 45000 lm |
| Colour temperature | 7200 K |
| Colour rendering index CRI | 70 Ra |
| Colour of light | 772 |

Safety information

| | |
|---------------------|--------------------------------------------|
| Safety instructions | www.nbb.cz |
|---------------------|--------------------------------------------|

Energetic characteristics

| | |
|---------------|-----------|
| Lamp efficacy | 75,0 lm/W |
|---------------|-----------|

Exclusion of liability

Changes to data are subject to prior notice. NBB Bohemia s.r.o. accepts no responsibility for damages caused by inaccurate interpretation of the content on this site.

Popis

Stage metal-halide lamps. Direct replacement MSR 575/2 SA/DE, HTI 575/D4/75, HMQ575/2 D4.

NBB Bohemia s.r.o., Sídliště 693, 407 22 Benešov nad Ploučnicí
<https://www.nbb.cz/en/> | hotmail@nbb.cz

Copyright CE 2024 NBB Bohemia s.r.o Všechna práva vyhrazena.