



NBB Bohemia s.r.o.

Výroba a prodej osvětlovací techniky, Sídliště 693, 407 22 Benešov nad Ploučnicí



Product Data Sheet

Metal-halogenidová výbojka

HLC-TD 150W/660 DW
UVS SUPER Pro® RX7s



Order number

740006010

Unit EAN13 code

8595209915641

General information

Model/Description	Vysokotlaká výbojka
Finish	Křemíková/Quartz
Brand/Manufacturer	NBB
Bulb finish	clear
Nominal service life (h)	15000 h
Model	Čirá
Socket	RX7s
Dimmable	Ano
Energy efficiency class (canceled regulation!)	A+
Lamp voltage	84 - 90 V
Dimmable by conventional dimmers	Ne
Název položky	HLC-TD 150W/660 DW UVS SUPER Pro® Rx7s

Electrical characteristics

Nominal wattage	150 W
Rated power (W)	150,0 W
Compatible ballast	1,8 A
Operating voltage (V)	86 V
Type of Voltage	AC
Pulse height	5 kV
Lamp operating current	0,8 A A
Direct connection to the mains	Ne
Lamp power	150 W
Nominal current (A)	1,80 A
Total power (W) (light fitting)	35 W

Working conditions

Ambiente temperature for max. luminous flux	max 180s/25°C °C
Hot restart	Ne
Bulb temperature (max.)	500 °C
Cap temperature (max.)	300 °C
Burning position	Libovolná
Application	Pro uzavřená svítidla
Burning position	Libovolná
External ignitor required	Ano
External ballast required	Ano
Material discharge tube	Křemíkový (Quartz)
Closed luminaire required	Ano

Physical characteristics

Dimensions (mm)	Ø24 x 135 mm
Packing method	10 - 1
Weight gross	40 g
Weight netto	30 g
Total lenght	135 mm
Diameter	24 mm
Lamp shape	Dvoupaticová válcová
Coated	Ne

EuP Parameters

Average Lifetime B50 (h)	15000 h
Luminescence Life maintenance factor	50,0 %
The rate of premature failures	<1 %
Rated service life	15000 h
Energy consumption (AGGR)	165 kWh/1000h
Turn-on time	max 30 s
Φ 90°	14000 lm

Lighting characteristics

Lenght of arc	4,8 mm
Color rendering	1B
Light Colour	denní bílá
Luminous flux	14000 lm
Colour temperature	6000 K
Colour rendering index CRI	65 Ra
Sun tanning lamp	Ne
Colour of light	660
Colour of light acc. EN 12464-1	Cool >5300 K
Chromaticity coordinates x	0,360
Chromaticity coordinates y	0,380

Radiation in the UV range

UV protect	Ano
------------	-----

Safety information

Safety instructions	www.nbb.cz
---------------------	--

Environmental characteristics

Maximum mercury content (mg)	max 4,00 mg
------------------------------	-------------

Energetic characteristics

Rated efficiency after 100h	99,8 %
Lamp efficacy	93,33 lm/W

Lamp survival factor (LSF)

LSF after 2.000 hrs	99,5 %
LSF after 6.000 hrs	95 %
LSF after 8.000 hrs	90 %
LSF after 9.000 hrs	80 %
LSF after 10.000 hrs	60 %
LSF after 12.000 hrs	50 %
LSF after 15.000 hrs	50 %

Lamp lumen maintenance factor (LLMF)

LLMF after 2.000 hrs	80 %
LLMF after 5.000 hrs	60 %
LLMF after 10.000 hrs	50 %
LLMF after 12.000 hrs	40 %
15.000 hrs	50 %

Exclusion of liability

Changes to data are subject to prior notice. NBB Bohemia s.r.o. accepts no responsibility for damages caused by inaccurate interpretation of the content on this site.

Popis

Quartz metal-halide lamps, Ra>65, TC 6000K, high output, life 15.000 h, UV-STOP.

NBB Bohemia s.r.o., Sídliště 693, 407 22 Benešov nad Ploučnicí
<https://www.nbb.cz/en/> | hotmail@nbb.cz

Copyright © 2024 NBB Bohemia s.r.o. Všechna práva vyhrazena.