



NBB Bohemia s.r.o.

Výroba a prodej osvětlovací techniky, Sídliště 693, 407 22 Benešov nad Ploučnicí



Product Data Sheet

Metal-halogenidová výbojka

JCL-TD 150W/830-930
UVS RX7s-24 JENBO

Order number

740121000

Unit EAN13 code

8595209921055



General information

Model/Description	Vysokotlaká výbojka
Finish	Keramická
Brand/Manufacturer	JENBO
Bulb finish	clear
Nominal service life (h)	15000 h
Model	Čirá
Socket	RX7s
Dimmable	Ano
Energy efficiency class (canceled regulation!)	A+
Lamp voltage	84 - 90 V
Dimmable by conventional dimmers	Ne
Název položky	JCL-TD 150W/830-930 UVS RX7s JENBO

Electrical characteristics

Nominal wattage	150 W
Rated power (W)	144 W
Compatible ballast	JENBO JB35
Operating voltage (V)	84 - 90 V
Type of Voltage	AC
Pulse height	5 kV
Lamp operating current	1,8 A A
Direct connection to the mains	Ne
Lamp power	150 W
Nominal current (A)	1,7 A
Total power (W) (light fitting)	35 W

Working conditions

Ambiente temperature for max. luminous flux	max 180s/25°C °C
Hot restart	Ne
Bulb temperature (max.)	500 °C
Cap temperature (max.)	300 °C
Burning position	Libovolná
Application	Pro uzavřená výbojková svítidla
Burning position	Libovolná
External ignitor required	Ano
External ballast required	Ano
Material discharge tube	Keramický
Closed luminaire required	Ano

Physical characteristics

Dimensions (mm)	Ø22 x 136 mm
Packing method	10 - 1
Weight gross	40 g
Weight netto	30 g
Total lenght	136 mm
Diameter	22 mm
Lamp shape	Dvoupaticová válcová
Coated	Ne

EuP Parameters

Average Lifetime B50 (h)	15000 h
Luminescence Life maintenance factor	50,0 %
The rate of premature failures	<1 %
Rated service life	15000 h
Energy consumption (AGGR)	158,4 kWh/1000h
Turn-on time	max 30 s
Φ 90°	13250 lm

Lighting characteristics

Lenght of arc	4,8 mm
Color rendering	1B
Light Colour	teplá bílá
Luminous flux	13250 lm
Colour temperature	3000 K
Colour rendering index CRI	94 Ra
Sun tanning lamp	Ne
Colour of light	830
Colour of light acc. EN 12464-1	Warm <3300 K
Chromaticity coordinates x	0,443
Chromaticity coordinates y	0,409

Radiation in the UV range

UV protect	Ano
------------	-----

Safety information

Safety instructions	www.nbb.cz
---------------------	--------------------------------------------

Environmental characteristics

Maximum mercury content (mg)	max 4,00 mg
------------------------------	-------------

Energetic characteristics

Rated efficiency after 100h	99,8 %
Lamp efficacy	88,33 lm/W

Lamp survival factor (LSF)

LSF after 2.000 hrs	99,5 %
LSF after 6.000 hrs	95 %
LSF after 8.000 hrs	90 %
LSF after 9.000 hrs	80 %
LSF after 10.000 hrs	60 %
LSF after 12.000 hrs	50 %
LSF after 15.000 hrs	50 %

Lamp lumen maintenance factor (LLMF)

LLMF after 2.000 hrs	80 %
LLMF after 5.000 hrs	60 %
LLMF after 10.000 hrs	50 %
LLMF after 12.000 hrs	40 %
15.000 hrs	50 %

Exclusion of liability

Changes to data are subject to prior notice. NBB Bohemia s.r.o. accepts no responsibility for damages caused by inaccurate interpretation of the content on this site.

Popis

Ceramic metal-halide lamps, longlife 15.000 h, Ra 90+, UV-stop, 13.250 lm, monolith burner.

NBB Bohemia s.r.o., Sídliště 693, 407 22 Benešov nad Ploučnicí
<https://www.nbb.cz/en/> | hotmail@nbb.cz

Copyright © 2024 NBB Bohemia s.r.o. Všechna práva vyhrazena.