



## Product Data Sheet

Žárovka pro digestoře

**ADR 240V 40W E14**  
**CLEAR RESISTA Lamp for**  
**cooker hoods (digestors)**  
**240V 40W E14**



Order number

**368010000**

Unit EAN13 code

**8595209900944**

### General information

Model/Description	<b>Vláknová žárovka</b>
Finish	<b>Pro digestoře</b>
Brand/Manufacturer	<b>NBB</b>
Nominal service life (h)	<b>1000 h</b>
Nominal voltage (V)	<b>24 V</b>
Model	<b>Čirá</b>
Socket	<b>E14</b>
Energy efficiency class (canceled regulation!)	<b>E</b>
Shock-proof	<b>Ne</b>
Krypton	<b>Ne</b>
Nominal voltage (V)	<b>230 - 240 V</b>
Multi-coiled filament	<b>Ano</b>
Lamp voltage	<b>230 - 240 V</b>
Dimmable by conventional dimmers	<b>Ano</b>
Název položky	<b>ADR 240V 40W E14 CLEAR RESISTA</b>
Třída energetické účinnosti podle 2019/2015	<b>G</b>

### Electrical characteristics

Nominal wattage	<b>40 W</b>
Rated power (W)	<b>38,9 W</b>
Operating voltage (V)	<b>220 - 240 V</b>
Type of Voltage	<b>AC/DC</b>
Direct connection to the mains	<b>Ano</b>
Nominal current	<b>160 mA</b>
Lamp power	<b>40 W</b>

Voltage type	AC/DC
Nominal current (A)	1,05 A
Total power (W) (light fitting)	40 W
<b>Working conditions</b>	
Bulb temperature (max.)	250 °C
Cap temperature (max.)	200 °C
Burning position	Libovolná
Suitable for domestic use.	Ne
Application	Elektrické spotřebiče
Suitable for baking oven	Ne
Suitable for refrigerator	Ano
Special application	Ostatní
<b>Physical characteristics</b>	
Dimensions (mm)	Ø25 x 82 mm
Packing method	1 - 10
Weight gross	15 g
Weight netto	8 g
Total length	82 mm
Diameter	25 mm
Splitter protection	Ne
Lamp shape	A55
Filament shape	CoiledCoil
Carbon filament	Ne
With vacuum	Ne
Number of filament supports	5
Fuses	1
<b>EuP Parameters</b>	
Average Lifetime B50 (h)	1000 h
Luminescence Life maintenance factor	80,0 %
The rate of premature failures	<1 %
Rated service life	1000 h
Energy consumption (AGGR)	40 kWh/1000h
<b>Lighting characteristics</b>	
Color rendering	1A
Luminous flux	400 lm
Colour temperature	2580 K
Colour rendering index CRI	100 Ra
Beam angle Degrees (°)	330 °
Chromaticity coordinates x	0,469
Chromaticity coordinates y	0,414
<b>Safety information</b>	
Safety instructions	<a href="http://www.nbb.cz">www.nbb.cz</a>

**Environmental characteristics**

Mercury content	0,00 mg
-----------------	---------

**Energetic characteristics**

Lamp efficacy	9,2 lm/W
Lamp displacement factor (DF)	1,00

**Lamp survival factor (LSF)**

LSF after 100 hrs	99,0 %
LSF after 1.000 hrs	50,0 %

**Exclusion of liability**

Changes to data are subject to prior notice. NBB Bohemia s.r.o. accepts no responsibility for damages caused by inaccurate interpretation of the content on this site.

**Popis**

Clear tubular lamps for kitchen hoods.

**NBB Bohemia s.r.o., Sídliště 693, 407 22 Benešov nad Ploučnicí**  
<https://www.nbb.cz/en/> | [hotmail@nbb.cz](mailto:hotmail@nbb.cz)  
Copyright CE 2024 NBB Bohemia s.r.o Všechna práva vyhrazena.