



## Product Data Sheet

Žárovka pro elektrický sporák

**ABO 240V 15W E14**  
**CLEAR 300°C NBB**

Order number

**370001010**

Unit EAN13 code

**8595209975720**



### General information

Model/Description	<b>Incandescent lamp</b>
Finish	<b>OVEN LAMP</b>
Brand/Manufacturer	<b>NARVA</b>
Nominal service life (h)	<b>1000 h</b>
Model	<b>Čirá</b>
Socket	<b>E14</b>
Energy efficiency class (canceled regulation!)	<b>E</b>
Shock-proof	<b>Ne</b>
Nominal voltage (V)	<b>230 - 240 V</b>
Lamp voltage	<b>230 - 240 V</b>
Dimmable by conventional dimmers	<b>Ano</b>
Název položky	<b>ABO 240V 15W E14 CLEAR 300°C</b>
Třída energetické účinnosti podle 2019/2015	<b>G</b>

### Electrical characteristics

Nominal wattage	<b>15 W</b>
Rated power (W)	<b>15 W</b>
Operating voltage (V)	<b>220 - 240 V</b>
Endurance	<b>300 V</b>
Type of Voltage	<b>AC/DC</b>
Nominal current	<b>63 mA</b>
Lamp power	<b>15 W</b>
Voltage type	<b>AC/DC</b>
Nominal current (A)	<b>0,063 A</b>
Total power (W) (light fitting)	<b>15 W</b>

### Working conditions

Bulb temperature (max.)	300 °C
Cap temperature (max.)	250 °C
Burning position	Libovolná
Suitable for domestic use.	Ne
Application	Elektrické spotřebiče
Suitable for baking oven	Ano
Suitable for refrigerator	Ano
Ambient temperature	0 - 300 °C

### Mounting methods/application

Mounting method	Electric household appliances
-----------------	-------------------------------

### Physical characteristics

Dimensions (mm)	22 x 48 mm
Packing method	1 - 10
Weight gross	12 g
Weight netto	10 g
Total length	48 mm
Diameter	22 mm
Carbon filament	Ne
Fuses	1

### EuP Parameters

Average Lifetime B50 (h)	1000 h
Luminescence Life maintenance factor	90 %
The rate of premature failures	<0,1 %
Rated service life	1000 h
Energy consumption (AGGR)	15 kWh/1000h

### Lighting characteristics

Luminous flux	85 lm
Colour temperature	2300 K
Colour rendering index CRI	100 Ra
Beam angle Degrees (°)	330 °

### Safety information

Safety instructions	<a href="http://www.nbb.cz">www.nbb.cz</a>
---------------------	--

### Energetic characteristics

Lamp efficacy	5,66 lm/W
Lamp displacement factor (DF)	1,00

### Exclusion of liability

Changes to data are subject to prior notice. NBB Bohemia s.r.o. accepts no responsibility for damages caused by inaccurate interpretation of the content on this site.

**NBB Bohemia s.r.o., Sídliště 693, 407 22 Benešov nad Ploučnicí**  
<https://www.nbb.cz/en/> | [hotmail@nbb.cz](mailto:hotmail@nbb.cz)

Copyright CE 2024 NBB Bohemia s.r.o Všechna práva vyhrazena.