



## Product Data Sheet

Otřesuvzdorná žárovka čirá

**AGR 240V 40W E27 A55**  
**CLEAR**

Order number

**337002010**

Unit EAN13 code

**8595209911766**


### General information

|  |   |
|--|---|
| Model/Description                              | <b>Incandescent lamp</b>                              |
| Finish   | <b>Žárovka otřesuvzdorná průmyslová</b>               |
| Brand/Manufacturer                             | <b>NBB</b>  |
| Lamp type                                      | <b>A55</b>  |
| Nominal service life (h)                       | <b>1000 h</b>   |
| Model  | <b>Čirá</b>   |
| Socket   | <b>E27</b>  |
| Energy efficiency class (canceled regulation!) | <b>E</b>  |
| Shock-proof                                    | <b>Ano</b>  |
| Krypton  | <b>Ne</b>   |
| Nominal voltage (V)                            | <b>230 - 240 V</b>                                    |
| Multi-coiled filament                          | <b>Ne</b>   |
| Lamp voltage                                   | <b>230 - 240 V</b>                                    |
| Dimmable by conventional dimmers               | <b>Ano</b>  |
| Název položky                                  | <b>AGR 240V A55 40W E27 CLEAR NBB (POUZE PRŮMYSL)</b> |
| Třída energetické účinnosti podle 2019/2015    | <b>G</b>  |

### Electrical characteristics

|                       |                             |
|-----------------------|-----------------------------|
| Nominal wattage       | <b>40 W</b>                 |
| Rated power (W)       | <b>40 W</b>                 |
| Operating voltage (V) | <b>220 - 240 V</b>          |
| Endurance             | <b>AC 300V/30h +/-10% V</b> |
| Type of Voltage       | <b>AC/DC</b>                |
| Lamp power            | <b>40 W</b>                 |
| Nominal current (A)   | <b>0,174 A</b>              |

**Working conditions**

|                           |                       |
|---------------------------|-----------------------|
| Bulb temperature (max.)   | 200 °C                |
| Cap temperature (max.)    | 150 °C                |
| Burning position          | Libovolná             |
| Application               | Všeobecné osvětlování |
| Suitable for baking oven  | Ne                    |
| Suitable for refrigerator | Ne                    |
| Special application       | Ostatní               |

**Physical characteristics**

|                             |             |
|-----------------------------|-------------|
| Dimensions (mm)             | Ø55 x 98 mm |
| Packing method              | 1 - 10      |
| Weight gross                | 30 g        |
| Weight netto                | 20 g        |
| Total lenght                | 98 mm       |
| Diameter                    | 55 mm       |
| Splitter protection         | Ne          |
| Lamp shape                  | Ostatní     |
| Carbon filament             | Ne          |
| Number of filament supports | 5           |

**EuP Parameters**

|                                |              |
|--------------------------------|--------------|
| Average Lifetime B50 (h)       | 1000 h       |
| The rate of premature failures | <2 %         |
| Rated service life             | 1000 h       |
| Energy consumption (AGGR)      | 40 kWh/1000h |

**Lighting characteristics**

|                            |        |
|----------------------------|--------|
| Color rendering            | 1A     |
| Luminous flux              | 370 lm |
| Colour rendering index CRI | 100 Ra |

**Safety information**

|                     |  |
|---------------------|--|
| Safety instructions | <a href="http://www.nbb.cz">www.nbb.cz</a> |
|---------------------|--|

**Environmental characteristics**

|                 |         |
|-----------------|---------|
| Mercury content | 0,00 mg |
|-----------------|---------|

**Energetic characteristics**

|               |        |
|---------------|--------|
| Lamp efficacy | 9 lm/W |
|---------------|--------|

**Lamp survival factor (LSF)**

|                     |        |
|---------------------|--------|
| LSF after 100 hrs   | 99,0 % |
| LSF after 1.000 hrs | 50,0 % |

**Exclusion of liability**

Changes to data are subject to prior notice. NBB Bohemia s.r.o. accepts no responsibility for damages caused by inaccurate

interpretation of the content on this site.

### **Popis**

Industrial shock resistance incandescent lamps for general lighting. Lifespan 1.000 h.

**NBB Bohemia s.r.o., Sídliště 693, 407 22 Benešov nad Ploučnicí**  
<https://www.nbb.cz/en/> | [hotmail@nbb.cz](mailto:hotmail@nbb.cz)

Copyright CE 2024 NBB Bohemia s.r.o Všechna práva vyhrazena.