



**NBB Bohemia s.r.o.**

Výroba a prodej osvětlovací techniky, Sídliště 693, 407 22 Benešov nad Ploučnicí



## Product Data Sheet

Třípásmová kruhová zářivka T5

**LC 32W T5/827 2GX13**  
**NBB**

Order number

**116632001**

Unit EAN13 code

**8595209950642**



### General information

Model/Description	<b>Zářivková trubice/Fluorescent lamps</b>
Finish	<b>Kruhová/Round shaped</b>
Brand/Manufacturer	<b>NBB</b>
Nominal service life (h)	<b>10000 h</b>
Socket	<b>2GX13</b>
Dimmable	<b>Ano</b>
Energy efficiency class (canceled regulation!)	<b>A</b>
Dimmable by conventional dimmers	<b>Ne</b>
Název položky	<b>5 - 827</b>

### Electrical characteristics

Nominal wattage	<b>32 W</b>
Rated power (W)	<b>32,0 W</b>
Operating voltage (V)	<b>125 V</b>
Type of Voltage	<b>AC</b>
Direct connection to the mains	<b>Ne</b>
Lamp power	<b>22 W</b>
Nominal current (A)	<b>0,192 A</b>

### Working conditions

Ambiente temperature for max. luminous flux	<b>35 °C</b>
Burning position	<b>Libovolná</b>
Application	<b>Všeobecné osvětlování</b>
Application	<b>Všeobecné osvětlení</b>
For application at low temperatures	<b>Ne</b>

### Physical characteristics

Dimensions (mm)	ø16,5 x 227,5 x 195,5 mm
Packing method	20 - 1
Weight gross	160 g
Weight netto	100 g
Splitter protection	Ne
Tube diameter	16 mm
Lamp shape	Kruhová
Internal reflector	Ne
Ring diameter	274 mm
Double-walled	Ne

### EuP Parameters

Average Lifetime B50 (h)	10000 h
Luminescence Life maintenance factor	89,0 %
The rate of premature failures	<1 %
Rated service life	10000 h
Energy consumption (AGGR)	35,2 kWh/1000h

### Lighting characteristics

Type of spectrum	Třípásmové
Color rendering	1B
Light Colour	teplá bílá komfort
Dominant wavelength	630 nm
Luminous flux	2152 lm
Colour temperature	2700 K
Colour rendering index CRI	82 Ra
Full spectrum lamps	Ne
Colour of light	827
Colour of light acc. EN 12464-1	Warm <3300 K
Beam angle Degrees (°)	360 °
Chromaticity coordinates x	0,444
Chromaticity coordinates y	0,396

### Safety information

Safety instructions	<a href="http://www.nbb.cz">www.nbb.cz</a>
---------------------	--

### Environmental characteristics

Mercury content	5,0 mg
-----------------	--------

### Energetic characteristics

Rated efficiency after 100h	99,99 %
Lamp efficacy	67 lm/W

### Lamp survival factor (LSF)

LSF after 2.000 hrs	99,5 %
---------------------	--------

LSF after 4.000 hrs	98,5 %
LSF after 8.000 hrs	82,0 %
LSF after 10.000 hrs	50,0 %

#### Lamp lumen maintenance factor (LLMF)

LLMF after 2.000 hrs	89,0 %
LLMF after 4.000 hrs	82,0 %
LLMF after 8.000 hrs	75,0 %
LLMF after 10.000 hrs	73,0 %

#### Exclusion of liability

Changes to data are subject to prior notice. NBB Bohemia s.r.o. accepts no responsibility for damages caused by inaccurate interpretation of the content on this site.

#### Warning

If broken in a closed room, we recommend ventilation to reduce the mercury vapor concentration. Use protective equipment while working. Immediately remove the shards so that they do not get injured. After removing the shards, use the technical means for decontamination of mercury. For this purpose we supply decontamination kits, which you can order by phone or in our internet shop. The decontamination kit should not be missed especially in plants where there is a danger of breaking light sources containing mercury, such as stores, warehouses, but can also be used in households. In case of nausea, give first aid and call a physician.

#### Notice

Fluorescent tubes of all types require a corresponding type of ballast to operate. A suitable ballast type can be found in the detail of the item (additional products). The quality and type of the ballast greatly affect the life of the fluorescent lamp. NBB Bohemia is not responsible for shortening lamp life when the fluorescent lamp is connected to a ballast type that NBB Bohemia s.r.o. because in such a case we can not guarantee the suitability of using the ballast to the supplied fluorescent tube. When directly connected to the mains voltage without using the ballast, the fluorescent lamp will be destroyed. Fluorescent tubes are not suitable for connection to motion sensors or for connection to frequent switching devices. Frequent switching causes shortening of lamp life. Frequent switching is considered to switch the fluorescent lamp to an interval of less than 20 minutes.

#### Popis

**NBB Bohemia s.r.o., Sídliště 693, 407 22 Benešov nad Ploučnicí**  
<https://www.nbb.cz/en/> | [hotmail@nbb.cz](mailto:hotmail@nbb.cz)

Copyright © 2024 NBB Bohemia s.r.o. Všechna práva vyhrazena.