



## Product Data Sheet

halogenová letištní žárovka

# Halogen Airfield Lamp PREFOCUS 6,6A 150W 6392LL PK30d



Order number

**551000050**

Unit EAN13 code

**4250686500035**

### General information

|                                  |  |
|----------------------------------|--|
| Specifications                   | <b>58368</b>   |
| Model/Description                | <b>Halogen Airfield Lamp with prefocus base</b>            |
| Finish                           | <b>Halogen</b>   |
| Brand/Manufacturer               | <b>VOSLA</b>   |
| Nominal service life (h)         | <b>2000 h</b>  |
| Nominal voltage (V)              | <b>22,7 V</b>  |
| Socket                           | <b>PK30d</b>   |
| Nominal voltage (V)              | <b>7 - 22 V</b>  |
| Dimmable by conventional dimmers | <b>ano</b>   |
| Název položky                    | <b>Letištní žár. PREFOCUS 6,6A 150W 6392LL 58368 PK30d</b> |

### Electrical characteristics

|                       |                 |
|-----------------------|-----------------|
| Nominal wattage       | <b>150 W</b>    |
| Rated power (W)       | <b>150 W</b>    |
| Operating voltage (V) | <b>7 - 22 V</b> |
| Type of Voltage       | <b>AC/DC</b>    |
| Power                 | <b>150 W</b>    |
| Nominal current (A)   | <b>6,6 A</b>    |

### Working conditions

|                         |                           |
|-------------------------|---------------------------|
| Bulb temperature (max.) | <b>350 °C</b>             |
| Cap temperature (max.)  | <b>250 °C</b>             |
| Burning position        | <b>S90</b>                |
| Application             | <b>Letecká návěstidla</b> |

## Physical characteristics

|                   |                               |
|-------------------|-------------------------------|
| Type of connector | flat male according DIN 46248 |
| Dimensions (mm)   | 56 x ø 13,5 mm                |
| Packing method    | 1 - 100                       |
| Weight netto      | 20 g                          |
| Total lenght      | 56 mm                         |
| Cable length      | min. 120 mm mm                |
| Diameter          | 13,5 mm                       |
| Lamp shape        | prefocus base                 |

## EuP Parameters

|                          |        |
|--------------------------|--------|
| Average Lifetime B50 (h) | 2000 h |
| Rated service life       | 2000 h |

## Lighting characteristics

|                            |         |
|----------------------------|---------|
| Luminous flux              | 3600 lm |
| Colour rendering index CRI | 100 Ra  |
| Beam angle Degrees (°)     | 360 °   |

## Safety information

|                     |  |
|---------------------|--|
| Safety instructions | <a href="http://www.nbb.cz">www.nbb.cz</a> |
|---------------------|--|

## Energetic characteristics

|               |         |
|---------------|---------|
| Lamp efficacy | 24 lm/W |
|---------------|---------|

## Exclusion of liability

Changes to data are subject to prior notice. NBB Bohemia s.r.o. accepts no responsibility for damages caused by inaccurate interpretation of the content on this site.

## Popis

**NBB Bohemia s.r.o., Sídliště 693, 407 22 Benešov nad Ploučnicí**  
<https://www.nbb.cz/en/> | [hotmail@nbb.cz](mailto:hotmail@nbb.cz)

Copyright CE 2024 NBB Bohemia s.r.o Všechna práva vyhrazena.