



## Product Data Sheet

Žárovka čirá

**AGL 230V A60 60W B22d  
CLEAR**



Order number

**334706052**

Unit EAN13 code

**8714101018193**

### General information

Model/Description	<b>Standardní žárovka</b>
Finish	<b>čirá</b>
Brand/Manufacturer	<b>NBB</b>
Nominal service life (h)	<b>1000 h</b>
Colour	<b>Čirá</b>
Model	<b>Čirá</b>
Socket	<b>B22d</b>
Energy efficiency class (canceled regulation!)	<b>E</b>
Shock-proof	<b>Ne</b>
Krypton	<b>Ne</b>
Nominal voltage (V)	<b>220 - 240 V</b>
Multi-coiled filament	<b>Ne</b>
Lamp voltage	<b>230 - 240 V</b>
Dimmable by conventional dimmers	<b>Ano</b>
Název položky	<b>AGL 230V A60 60W B22d čirá</b>

### Electrical characteristics

Nominal wattage	<b>60 W</b>
Rated power (W)	<b>60 W</b>
Operating voltage (V)	<b>220 - 240 V</b>
Endurance	<b>300V/30 h V</b>
Type of Voltage	<b>AC/DC</b>
Direct connection to the mains	<b>Ano</b>
Lamp power	<b>60 W</b>
Nominal current (A)	<b>0,26 A</b>

### Working conditions

Bulb temperature (max.)	200 °C
Cap temperature (max.)	150 °C
Burning position	Libovolná
Suitable for domestic use.	Ne
Application	Všeobecné osvětlování/General lighting
Suitable for baking oven	Ne
Suitable for refrigerator	Ne
Special application	Ostatní

### Physical characteristics

Dimensions (mm)	Ø60 x 103 mm
Packing method	25 - 1
Weight gross	50 g
Weight netto	30 g
Total length	103 mm
Diameter	60 mm
Splitter protection	Ne
Lamp shape	Ostatní
Carbon filament	Ne
Number of filament supports	5

### EuP Parameters

Average Lifetime B50 (h)	1000 h
Luminescence Life maintenance factor	80 %
The rate of premature failures	1 %
Rated service life	1000 h
Energy consumption (AGGR)	60 kWh/1000h

### Lighting characteristics

Color rendering	1A
Luminous flux	715 lm
Colour rendering index CRI	100 Ra
Chromaticity coordinates x	0,463
Chromaticity coordinates y	0,411

### Safety information

Safety instructions	<a href="http://www.nbb.cz">www.nbb.cz</a>
---------------------	--

### Environmental characteristics

Mercury content	0,00 mg
-----------------	---------

### Energetic characteristics

Lamp efficacy	11,9 lm/W
---------------	-----------

### Lamp survival factor (LSF)

LSF after 100 hrs	99,0 %
-------------------	--------

LSF after 1.000 hrs	50,0 %
---------------------	--------

#### **Exclusion of liability**

Changes to data are subject to prior notice. NBB Bohemia s.r.o. accepts no responsibility for damages caused by inaccurate interpretation of the content on this site.

#### **Popis**

Clear incandescent lamps for general lighting. Lifespan 1.000 h.

**NBB Bohemia s.r.o., Sídliště 693, 407 22 Benešov nad Ploučnicí**  
<https://www.nbb.cz/en/> | [hotmail@nbb.cz](mailto:hotmail@nbb.cz)

Copyright CE 2024 NBB Bohemia s.r.o Všechna práva vyhrazena.