



Product Data Sheet

Nízkovoltová žárovka čirá

**AGN 24V A55 60W E27
CLEAR**



Order number

339003000

Unit EAN13 code

8595209901033

General information

| | |
|--|-----------------------------------|
| Model/Description | Žárovka/Incandescent lamps |
| Finish | Čirá/Clear |
| Brand/Manufacturer | NBB |
| Nominal service life (h) | 1000 h |
| Nominal voltage (V) | 24 V |
| Model | Čirá |
| Socket | E27 |
| Energy efficiency class (canceled regulation!) | E |
| Shock-proof | Ano |
| Krypton | Ne |
| Nominal voltage (V) | 24 V |
| Multi-coiled filament | Ano |
| Lamp voltage | 24 V |
| Dimmable by conventional dimmers | Ano |
| Název položky | AGN 24V A55 60W E27 ČIRÁ |
| Třída energetické účinnosti podle 2019/2015 | G |

Electrical characteristics

| | |
|--------------------------------|------------------|
| Nominal wattage | 60 W |
| Rated power (W) | 60 W |
| Operating voltage (V) | 22 - 24 V |
| Type of Voltage | AC/DC |
| Direct connection to the mains | Ne |
| Lamp power | 60 W |
| Voltage type | AC/DC |

| | |
|---------------------------------|-------|
| Nominal current (A) | 2,5 A |
| Total power (W) (light fitting) | 60 W |

Working conditions

| | |
|----------------------------|--|
| Bulb temperature (max.) | 200 °C |
| Cap temperature (max.) | 150 °C |
| Burning position | Libovolná |
| Suitable for domestic use. | Ne |
| Application | Všeobecné osvětlování/General lighting |
| Suitable for baking oven | Ne |
| Suitable for refrigerator | Ne |
| Special application | Ostatní |

Physical characteristics

| | |
|-----------------------------|-------------|
| Dimensions (mm) | Ø55 x 98 mm |
| Packing method | 100 - 10 |
| Weight gross | 30 g |
| Weight netto | 20 g |
| Total lenght | 98 mm |
| Diameter | 55 mm |
| Splitter protection | Ne |
| Lamp shape | Ostatní |
| Filament shape | CoiledCoil |
| Carbon filament | Ne |
| With vacuum | Ne |
| Number of filament supports | 5 |

EuP Parameters

| | |
|--------------------------------------|--------------|
| Average Lifetime B50 (h) | 1000 h |
| Luminescence Life maintenance factor | 80,0 % |
| The rate of premature failures | <2 % |
| Rated service life | 1000 h |
| Energy consumption (AGGR) | 60 kWh/1000h |

Lighting characteristics

| | |
|----------------------------|--------|
| Color rendering | 1A |
| Luminous flux | 715 lm |
| Colour temperature | 2520 K |
| Colour rendering index CRI | 100 Ra |
| Chromaticity coordinates x | 0,460 |
| Chromaticity coordinates y | 0,410 |

Safety information

| | |
|---------------------|--|
| Safety instructions | www.nbb.cz |
|---------------------|--|

Environmental characteristics

| | |
|-----------------|---------|
| Mercury content | 0,00 mg |
|-----------------|---------|

Energetic characteristics

| | |
|-------------------------------|---------|
| Lamp efficacy | 12 lm/W |
| Lamp displacement factor (DF) | 1,00 |

Lamp survival factor (LSF)

| | |
|---------------------|--------|
| LSF after 100 hrs | 99,0 % |
| LSF after 1.000 hrs | 50,0 % |

Exclusion of liability

Changes to data are subject to prior notice. NBB Bohemia s.r.o. accepts no responsibility for damages caused by inaccurate interpretation of the content on this site.

Popis

Industrial 24V incandescent lamps for general lighting. Lifespan 1.000 h.

NBB Bohemia s.r.o., Sídliště 693, 407 22 Benešov nad Ploučnicí
<https://www.nbb.cz/en/> | hotmail@nbb.cz

Copyright CE 2024 NBB Bohemia s.r.o Všechna práva vyhrazena.