



NBB Bohemia s.r.o.

Výroba a prodej osvětlovací techniky, Sídliště 693, 407 22 Benešov nad Ploučnicí



Product Data Sheet

Nízkovoltová žárovka čirá

AGN 42V A55 60W E27
clear



Order number

339014000

Unit EAN13 code

8595209901569

General information

Model/Description	Žárovka/Incandescent lamps
Finish	Čirá/Clear
Brand/Manufacturer	NBB
Nominal service life (h)	1000 h
Nominal voltage (V)	42 V
Model	Čirá
Socket	E27
Energy efficiency class (canceled regulation!)	E
Shock-proof	Ano
Krypton	Ne
Nominal voltage (V)	42 V
Multi-coiled filament	Ano
Lamp voltage	42 V
Dimmable by conventional dimmers	Ano
Název položky	AGN 42V A55 60W E27 CLEAR
Třída energetické účinnosti podle 2019/2015	G

Electrical characteristics

Nominal wattage	60 W
Rated power (W)	60 W
Operating voltage (V)	40 - 42 V
Type of Voltage	AC/DC
Direct connection to the mains	Ne
Lamp power	60 W
Voltage type	AC/DC

Nominal current (A)	1,43 A
Total power (W) (light fitting)	60 W

Working conditions

Bulb temperature (max.)	200 °C
Cap temperature (max.)	150 °C
Burning position	Libovolná
Suitable for domestic use.	Ne
Application	Průmyslové aplikace
Suitable for baking oven	Ne
Suitable for refrigerator	Ne
Special application	Ostatní

Physical characteristics

Dimensions (mm)	Ø55 x 98 mm
Packing method	1 - 100
Weight gross	30 g
Weight netto	20 g
Total lenght	98 mm
Diameter	55 mm
Splitter protection	Ne
Lamp shape	Ostatní
Filament shape	CoiledCoil
Carbon filament	Ne
With vacuum	Ne
Number of filament supports	5

EuP Parameters

Average Lifetime B50 (h)	1000 h
Luminescence Life maintenance factor	80,0 %
The rate of premature failures	<2 %
Rated service life	1000 h
Energy consumption (AGGR)	60 kWh/1000h

Lighting characteristics

Color rendering	1A
Luminous flux	715 lm
Colour temperature	2580 K
Colour rendering index CRI	100 Ra
Chromaticity coordinates x	0,460
Chromaticity coordinates y	0,410

Safety information

Safety instructions	www.nbb.cz
---------------------	--

Environmental characteristics

Mercury content	0,00 mg
-----------------	---------

Energetic characteristics

Lamp efficacy	12 lm/W
Lamp displacement factor (DF)	1,00

Lamp survival factor (LSF)

LSF after 100 hrs	99,0 %
LSF after 1.000 hrs	50,0 %

Exclusion of liability

Changes to data are subject to prior notice. NBB Bohemia s.r.o. accepts no responsibility for damages caused by inaccurate interpretation of the content on this site.

Popis

Industrial 42V incandescent lamps for general lighting. Lifespan 1.000 h.

NBB Bohemia s.r.o., Sídliště 693, 407 22 Benešov nad Ploučnicí
<https://www.nbb.cz/en/> | hotmail@nbb.cz

Copyright CE 2024 NBB Bohemia s.r.o Všechna práva vyhrazena.