



Product Data Sheet

Projekční halogenová žárovka

PAR 64 CP87 240V/500W
NSP GX16d 300h.



Order number

520000095

Unit EAN13 code

8595209938220

General information

Model/Description	Halogenová žárovka/Halogen Lamp
Finish	Projekční/Projection
Brand/Manufacturer	NBB
Lamp type	PAR64
Nominal service life (h)	300 h
Socket	Ostatní
Nominal voltage (V)	230 - 240 V
Lamp voltage	220 - 240 V
Dimmable by conventional dimmers	Ano
Název položky	PAR 64 CP87 240V/500W NSP GX16d 300h.

Electrical characteristics

Nominal wattage	500 W
Rated power (W)	500 W
Operating voltage (V)	220 - 240 V
Lamp power	500 W
Voltage type	AC/DC
Technology	Halogen
Nominal current (A)	2,1 A

Working conditions

Bulb temperature (max.)	400 °C
Cap temperature (max.)	400 °C
Burning position	Libovolná
Application	Studiové osvětlování a projekční technika

Physical characteristics

M.O.L.	5,91 mm
Dimensions (mm)	Ø203 x 152 mm
Packing method	1 - 6
Weight gross	862 g
Weight netto	764 g
Total lenght	152 mm
Diameter	203 mm
Lamp shape	PAR 64
Filament shape	Single filament
Filament length	9 mm
Reflector diameter	203 mm

EuP Parameters

Average Lifetime B50 (h)	300 h
Rated service life	300 h

Lighting characteristics

Luminous intensity	176700 Cd
Dominant wavelength	758 nm
Luminous flux	9500 lm
Colour temperature	3200 K
Colour rendering index CRI	100 Ra
Maximal intensity (Cd)	176700 Cd
Cool beam	Ne
Beam angle Degrees (°)	19 °
Chromaticity coordinates x	0,440
Chromaticity coordinates y	0,407

Safety information

Safety instructions	www.nbb.cz
---------------------	--

Exclusion of liability

Changes to data are subject to prior notice. NBB Bohemia s.r.o. accepts no responsibility for damages caused by inaccurate interpretation of the content on this site.

Popis

Theater reflector lamp with smooth galss, beam angle 19°.

NBB Bohemia s.r.o., Sídliště 693, 407 22 Benešov nad Ploučnicí
<https://www.nbb.cz/en/> | hotmail@nbb.cz

Copyright CE 2024 NBB Bohemia s.r.o Všechna práva vyhrazena.