



NBB Bohemia s.r.o.

Výroba a prodej osvětlovací techniky, Sídliště 693, 407 22 Benešov nad Ploučnicí



Product Data Sheet

Přijímač pro bezdrátové stmívání ED

RF receiver EasyDiM 4x5A (12-36VDC) CV



Order number

SR-2501N

Unit EAN13 code

8595209918734

General information

Specifications	SR-2501N
Model/Description	RF přijímač pro stmívání LED /RF receiver
Brand/Manufacturer	SUNRICHER
Material	Plastic/plast
Lamp type	LED napájené konstantním napětím
Degree of protection (IP)	IP20
Colour	Bílá
Dimmable	Ano
Nominal voltage (V)	12 - 36 V
Number of channels	4
Název položky	RF přijímač EasyDiM 4x5A (12-36VDC) CV

Electrical characteristics

Nominal wattage	4x(60-180) W
Maximal current load	4 x 5A A
Operating voltage (V)	12 - 36 V
Type of Voltage	DC
Nominal current (A)	5 A

Working conditions

Function	Stmívání, spínání
Wire	1,5 mm²
Dimmable range	1 - 100 %
Working temperature of the ballast body -Tc max	75 °C
Burning position	Libovolná

Application	Přijímač-stmívač
Halogen free	Ano
Material quality	Termoplast
Ambient temperature	-20/+50 °C
Suitable for movement sensor	Ne
Signal transmission	Radio-frekvenční
Manual transmitter	Ne
Wall-mounted transmitter	Ne
Suitable for switch	Ano
Suitable for dimmer	Ano
Dálkové ovládání	Ano
Suitable for venetian shutter switch	Ne
Okenní vysílač	Ne
Suitable for indication element	Ne
Počet spínaných zón	1

Mounting methods/application

Mounting method	Na omítku
-----------------	------------------

Physical characteristics

Number of couplings	4
Type of connector	Screw/šroubky
Dimensions (mm)	177 x 46 x 20 mm
Packing method	1
Spacing of fixing holes	172 mm
Surface protection	Bez úpravy
Weight netto	110 g
Material	Plast
RAL-number (akin)	9001
Transparent	Ne
Type of surface	Matný

EuP Parameters

The rate of premature failures	<1 %
The product to be used as (LED) light source controller	Ano

Safety information

Insulation class	Třída III
Safety instructions	www.nbb.cz

Exclusion of liability

Changes to data are subject to prior notice. NBB Bohemia s.r.o. accepts no responsibility for damages caused by inaccurate interpretation of the content on this site.

Notice

Under the scope of Act 185/2001 Coll. as amended, this product is included in waste group 5 (light sources and luminaires). In view of the harmful effects of mercury on the environment and on human health, the creators of group 5 waste (consumers) are obliged to dispose of used light sources for recycling. Do not throw this product into mixed waste after use. Take it to the nearest store, collection yard, or other designated location for free recycling. You can also dispose of the used products for recycling in our sales outlets or in collection points of collective recycling systems or municipal collection yards. Ecological

recycling of waste electrical and electronic equipment is ensured through the RETELA collective system (www.retela.cz).

Notice

Single LED chip failure, luminous flux deviation +/- 10% as well as chromaticity deviation +/- 150K are in compliance with applicable standards and are not a reason for complaint.

Popis

RF receiver-dimmer. 12-36V DC, 4 outputs 5A, 4x(60-180W). IP20. Constant voltage (CV).

NBB Bohemia s.r.o., Sídliště 693, 407 22 Benešov nad Ploučnicí
<https://www.nbb.cz/en/> | hotmail@nbb.cz

Copyright CE 2024 NBB Bohemia s.r.o. Všechna práva vyhrazena.