



Product Data Sheet

Přijímač pro bezdrátové stmívání ED

RF receiver EasyDiM 4x8A (12-36DC) CV



Order number

SR-2501NEA

Unit EAN13 code

8595209936851

General information

| | |
|---------------------------|--|
| Specifications | SR-2501NEA |
| Model/Description | RF přijímač pro stmívání LED /RF receiver |
| Brand/Manufacturer | SUNRICHER |
| Material | Plastic/plast |
| Lamp type | LED napájené konstantním napětím |
| Degree of protection (IP) | IP20 |
| Colour | Bílá |
| Dimmable | Ano |
| Nominal voltage (V) | 12 - 36 V |
| Number of channels | 4 |
| Název položky | RF přijímač EasyDiM 4x8A (12-36VDC) CV |

Electrical characteristics

| | |
|-----------------------|---------------------|
| Nominal wattage | 4x(96-288) W |
| Maximal current load | 8 A |
| Operating voltage (V) | 12 - 36 V |
| Type of Voltage | DC |
| Nominal current (A) | 8 A |

Working conditions

| | |
|---|---------------------------|
| Learning Key | Ano |
| Function | Stmívání, spínání |
| Wire | 1,5 mm² |
| Dimmable range | 1 - 100 % |
| Working temperature of the ballast body -Tc max | 75 °C |

| | |
|--------------------------------------|------------------|
| Burning position | Libovolná |
| Application | Přijímač-stmívač |
| Halogen free | Ano |
| Material quality | Termoplast |
| Ambient temperature | -20/+50 °C |
| Suitable for movement sensor | Ne |
| Signal transmission | Radio-frekvenční |
| Manual transmitter | Ne |
| Wall-mounted transmitter | Ne |
| Suitable for switch | Ano |
| Suitable for dimmer | Ano |
| Dálkové ovládání | Ano |
| Suitable for venetian shutter switch | Ne |
| Okenní vysílač | Ne |
| Suitable for indication element | Ne |
| Počet spínaných zón | 1 |

Mounting methods/application

| | |
|-----------------|-----------|
| Mounting method | Na omítku |
|-----------------|-----------|

Physical characteristics

| | |
|-------------------------|------------------|
| Type of connector | Screw/šroubky |
| Dimensions (mm) | 177 x 46 x 20 mm |
| Packing method | 1 |
| Spacing of fixing holes | 172 mm |
| Surface protection | Bez úpravy |
| Weight netto | 110 g |
| Material | Plast |
| RAL-number (akin) | 9001 |
| Transparent | Ne |
| Type of surface | Matný |

EuP Parameters

| | |
|---|------|
| The rate of premature failures | <1 % |
| The product to be used as (LED) light source controller | Ano |

Safety information

| | |
|---------------------|--|
| Insulation class | Třída III |
| Safety instructions | www.nbb.cz |

Exclusion of liability

Changes to data are subject to prior notice. NBB Bohemia s.r.o. accepts no responsibility for damages caused by inaccurate interpretation of the content on this site.

Notice

Under the scope of Act 185/2001 Coll. as amended, this product is included in waste group 5 (light sources and luminaires). In view of the harmful effects of mercury on the environment and on human health, the creators of group 5 waste (consumers) are obliged to dispose of used light sources for recycling. Do not throw this product into mixed waste after use. Take it to the nearest store, collection yard, or other designated location for free recycling. You can also dispose of the used products for recycling in our sales outlets or in collection points of collective recycling systems or municipal collection yards. Ecological

recycling of waste electrical and electronic equipment is ensured through the RETELA collective system (www.retela.cz).

Notice

Single LED chip failure, luminous flux deviation +/- 10% as well as chromaticity deviation +/- 150K are in compliance with applicable standards and are not a reason for complaint.

Popis

NBB Bohemia s.r.o., Sídliště 693, 407 22 Benešov nad Ploučnicí
<https://www.nbb.cz/en/> | hotmail@nbb.cz

Copyright CE 2024 NBB Bohemia s.r.o. Všechna práva vyhrazena.