



## Product Data Sheet

Bezdrátový ovladač osvětlení LED

# SR-2807R



Order number

**SR-2807R**

Unit EAN13 code

**8595209941015**

### General information

|                    |   |
|--------------------|---|
| Model/Description  | <b>SR-2807R</b>                           |
| Finish             | <b>Kulatý/Round</b>                       |
| Brand/Manufacturer | <b>Sunricher</b>                          |
| Material           | <b>Plast/plastic</b>                      |
| Colour             | <b>Stříbrná</b>                           |
| Number of channels | <b>1</b>                                  |
| Transmission range | <b>20 m</b>                               |
| Název položky      | <b>RF kapesní ovladač 1 zóna (kulatý)</b> |

### Working conditions

|                                      |   |
|--------------------------------------|---|
| Function                             | <b>Spínání/Switch, Stmívání/Dimming</b> |
| Burning position                     | <b>Libovolná</b>                        |
| Application                          | <b>Vysílač-ovladač</b>                  |
| Halogen free                         | <b>Ano</b>                              |
| Material quality                     | <b>Termoplast</b>                       |
| Suitable for movement sensor         | <b>Ne</b>                               |
| Signal transmission                  | <b>Radio-frekvenční</b>                 |
| Manual transmitter                   | <b>Ne</b>                               |
| Wall-mounted transmitter             | <b>Ne</b>                               |
| Suitable for switch                  | <b>Ano</b>                              |
| Suitable for dimmer                  | <b>Ano</b>                              |
| Dálkové ovládání                     | <b>Ano</b>                              |
| Suitable for venetian shutter switch | <b>Ne</b>                               |
| Okenní vysílač                       | <b>Ne</b>                               |
| Suitable for indication element      | <b>Ne</b>                               |

## Mounting methods/application

|                 |         |
|-----------------|---------|
| Mounting method | Ostatní |
|-----------------|---------|

## Physical characteristics

|                    |               |
|--------------------|---------------|
| Dimensions (mm)    | ø32,2 x 12 mm |
| Packing method     | 1             |
| Surface protection | Bez úpravy    |
| Weight netto       | 30 g          |
| Material           | Plast         |
| RAL-number (akin)  | 9001          |
| Transparent        | Ne            |
| Type of surface    | Matný         |

## EuP Parameters

|   |       |
|---|-------|
| The rate of premature failures                          | <1' % |
| The product to be used as (LED) light source controller | Ano   |

## Safety information

|                     |  |
|---------------------|--|
| Safety instructions | <a href="http://www.nbb.cz">www.nbb.cz</a> |
|---------------------|--|

## Exclusion of liability

Changes to data are subject to prior notice. NBB Bohemia s.r.o. accepts no responsibility for damages caused by inaccurate interpretation of the content on this site.

## Notice

Under the scope of Act 185/2001 Coll. as amended, this product is included in waste group 5 (light sources and luminaires). In view of the harmful effects of mercury on the environment and on human health, the creators of group 5 waste (consumers) are obliged to dispose of used light sources for recycling. Do not throw this product into mixed waste after use. Take it to the nearest store, collection yard, or other designated location for free recycling. You can also dispose of the used products for recycling in our sales outlets or in collection points of collective recycling systems or municipal collection yards. Ecological recycling of waste electrical and electronic equipment is ensured through the RETELA collective system ([www.retela.cz](http://www.retela.cz)).

## Notice

Single LED chip failure, luminous flux deviation +/- 10% as well as chromaticity deviation +/- 150K are in compliance with applicable standards and are not a reason for complaint.

## Popis

NBB Bohemia s.r.o., Sídliště 693, 407 22 Benešov nad Ploučnicí  
<https://www.nbb.cz/en/> | [hotmail@nbb.cz](mailto:hotmail@nbb.cz)

Copyright CE 2024 NBB Bohemia s.r.o. Všechna práva vyhrazena.