



Product Data Sheet

Kancelářské zářivkové svítidlo

TAUR T5 2x35 G5 EVG PAR IP20



Order number

910710015

Unit EAN13 code

8595209943392

General information

Model/Description	Zářivkové svítidlo
Brand/Manufacturer	NBB
Material	Plech
Lamp type	T5
Nominal service life (h)	50000 h
Degree of protection (IP)	IP20
Dimmable	Ne
Lamp type	Zářivka T5 (16mm)
Nominal voltage (V)	230 - 240 V
Degree of protection (IP)	IP20
Suitable for number of lamps	2
Dimmable by conventional dimmers	Ne
Název položky	TAUR T5 2x35 EVG PAR IP20

Electrical characteristics

Nominal wattage	2 x 35 W
Operating voltage (V)	220 - 240 V
Type of Voltage	AC
Lowest permitted operating voltage (V)	190 V
Lamp power	35 W
Circuit	Paralelně-kompenzační
Voltage type	AC
Lamp power at multiwatt	Ostatní
Nominal current (A)	0,304 A

Working conditions

Output frequency of ballast (driver)	40 kHz
Operating frequency	50 - 60 Hz
Light source is part of the fixture	Ne
Working temperature of the ballast body -Tc max	70 °C
Hot restart	Ano
Protection against overvoltage	Ano
Burning position	Horizontální
Installation height (m)	2 - 4 m
Application	Všeobecné osvětlování/General lighting
Suitable for through-wiring	Ne
Lamp holder type	G5
Type of control gear	Elektronický nestmívatelný
Suitable for light line configuration	Ne
Suitable for emergency lighting	Ne
Fire resistance "D"	Ano
Suspension supplied with the product	Ano
Fit for monitor workplace	Ano
Type of dimming	Nestmívatelné
Emergency unit integrated	Ne

Physical characteristics

Numbers of ballasts	1
Dimensions (mm)	1490 x 144 x 114 mm
Packing method	1 - 4
Weight gross	3550 g
Width	144 mm
Reflector	Vysoce leštěný
Height	114 mm
Colour housing	Stříbrná
Weight netto	3170 g
Type of grid	Vysoce leštěná
Length	1539 mm
Material housing	Aluminium
Impact strength	IK06
Type of surface	Matný

EuP Parameters

Average Lifetime B50 (h)	50000 h
Bulb type (size) for which is the luminaire designed.	T5
Number of maximal switching cycles	50000
The rate of premature failures	<1 %
Rated service life	50000 h
Turn-on time	<1 s

Additional information

With lamp	Ne
-----------	----

Lighting characteristics

Direct-/indirect proportion separately controllable	Ano
Light outlet	Přímé
Light sharing	Symetrické
Colour	Bílá

Safety information

Insulation class	třída I
Safety instructions	www.nbb.cz
Protection class	Ochranným vodičem

Energetic characteristics

Energy Efficiency Index	A2
Lamp Power factor (PF)	0,98

Exclusion of liability

Changes to data are subject to prior notice. NBB Bohemia s.r.o. accepts no responsibility for damages caused by inaccurate interpretation of the content on this site.

Notice

This product ranks among electrotechnical products powered by mains voltage 230-240V. For safety reasons, it is recommended that the assembly, connection or disassembly be carried out by a person with an appropriate electrotechnical qualification. Please note that the product may only be put into service with original covers, otherwise there may be a risk of electric shock, especially from the terminal block. Only use the product in places that are suitable for this purpose; do not use products intended for indoor use only in the outdoor environment. When installing or dismantling an emergency luminaire, we recommend disconnecting the power supply otherwise there may be a risk of electric shock. Observe the prescribed position when operating the product and how it is attached. Only connect the product to the rated voltage, or load it only to the maximum permitted power. Install only light sources for this type of luminaire. The manufacturer can not be held responsible for damages resulting from inappropriate connection, connection to an unsuitable distribution system, or damage resulting from the use of an unsuitable light source. Observe the operating values on the label. Do not expose the product to inappropriate weathering or high temperatures unless it is expressly stated that the product is intended to be operated under these conditions. When installing, wiring or disassembling, follow the generally accepted safety precautions.

NOTICE:

The emergency luminaire is energized even after disconnecting the power supply due to its own charged batteries. Therefore, it is recommended that the installation and disassembly be carried out only by a person with the appropriate electrotechnical qualifications.

Do not throw the emergency luminaire into the mixed waste after use. Take it to the nearest store, collection yard, or other designated location for free recycling. You can also deliver the used luminaires for recycling at our sales outlets. Emergency lights and modules contain a rechargeable battery. You can find the list of collection points on the Retel and Ekolamp Collective Systems pages.

Popis

Fluorescent interior suspended luminaire for T5 fluorescent lamps. Hanging cables are included. Length 1540 mm.

NBB Bohemia s.r.o., Sídliště 693, 407 22 Benešov nad Ploučnicí
<https://www.nbb.cz/en/> | hotmail@nbb.cz

Copyright CE 2024 NBB Bohemia s.r.o Všechna práva vyhrazena.