



Product Data Sheet

Bodové svítidlo

**Spot fixture 230-240V
ROMA PG/N**



Order number

910000305

Unit EAN13 code

8595209918215

General information

| | |
|---------------------------------|---|
| Model/Description | Bodové svítidlo |
| Finish | Vestavné pevné |
| Brand/Manufacturer | NBB |
| Material | Kov/Metal |
| Lamp type | MR16, GU10 |
| Degree of protection (IP) | IP20 |
| Built-in depth | 70 mm |
| Max. lamp power | 50 W |
| With light sensor | Ne |
| Suitable for suspended mounting | Ne |
| Lamp type | LED |
| Nominal voltage (V) | 0 - 50 V |
| Degree of protection (IP) | IP20 |
| Suitable for number of lamps | 1 |
| Suitable for wall mounting | Ne |
| Suitable for built-in mounting | Ano |
| Control gear included | Ne |
| Suitable for surface mounting | Ne |
| Suitable for ceiling mounting | Ano |
| Název položky | Bodové svítidlo ROMA PG/N Max 50W IP20 |

Electrical characteristics

| | |
|-----------------------|-----------------|
| Nominal wattage | max 50 W |
| Operating voltage (V) | 0 - 50 V |
| Type of Voltage | AC/DC |

| | |
|---------------------------------|----------|
| Voltage type | AC/DC |
| Suitable for lamp power | 0 - 50 W |
| Lamp power at multiwatt | Ostatní |
| Nominal current (A) | 2 A |
| System power | 50 W |
| Total power (W) (light fitting) | 50 W |

Working conditions

| | |
|---|-----------------------|
| Integrated driver | Ne |
| Burning position | Libovolná |
| Suitable for domestic use. | Ano |
| Installation on flammable surfaces | Ano |
| Application | Všeobecné osvětlování |
| Lamp holder type | GU5.3 |
| With movement sensor | Ne |
| Ambient temperature | -20/+50 °C |
| Fire resistance "D" | Ano |
| Fit for monitor workplace | Ano |
| Type of dimming | Ostatní |
| Emergency unit integrated | Ne |
| Filament test according to IEC 60695-2-10 | Neuvedeno |
| Driver included | Ne |

Mounting methods/application

| | |
|---------------------------------|----------|
| Dimensions of installation hole | Ø55 mm |
| Mounting method | Vestavná |

Physical characteristics

| | |
|-------------------|----------------------|
| Dimensions (mm) | Ø82 x 31 mm |
| Packing method | 1 |
| Weight gross | 67 g |
| Outer diameter | 82 mm |
| Colour housing | Zlatá |
| Weight netto | 40 g |
| Built-in diameter | 55 mm |
| Height/depth (mm) | 31 mm |
| Material housing | Ocelový plech |
| Impact strength | IK10 |
| Type of surface | Matný |
| Adjustability | Pevné nenastavitelné |

Additional information

| | |
|-----------|------------------------------------|
| Note | Standardně dodáváno s paticí GU5,3 |
| With lamp | Ne |

Lighting characteristics

| | |
|--------------|-------|
| Light outlet | Přímé |
|--------------|-------|

Light sharing

Symetrické

Safety information

Safety instructions

www.nbb.cz

Protection class

Bezpečným napětím

Exclusion of liability

Changes to data are subject to prior notice. NBB Bohemia s.r.o. accepts no responsibility for damages caused by inaccurate interpretation of the content on this site.

Popis

Firm spotlight for halogen and LED light sources. GOLDEN/NICKEL finish, socket G5.3 or GU10

NBB Bohemia s.r.o., Sídliště 693, 407 22 Benešov nad Ploučnicí
<https://www.nbb.cz/en/> | hotmail@nbb.cz

Copyright CE 2024 NBB Bohemia s.r.o Všechna práva vyhrazena.