



**NBB Bohemia s.r.o.**

Výroba a prodej osvětlovací techniky, Sídliště 693, 407 22 Benešov nad Ploučnicí



## Product Data Sheet

Bodové svítidlo

**Spot fixture 230-240V  
MILANO CHROME**



Order number

**910000015**

Unit EAN13 code

**8595209918086**

### General information

Model/Description	<b>Bodové svítidlo</b>
Finish	<b>Vestavné pevné</b>
Brand/Manufacturer	<b>NBB</b>
Material	<b>Kov/Metal</b>
Lamp type	<b>MR16, GU10</b>
Degree of protection (IP)	<b>IP20</b>
Built-in depth	<b>70 mm</b>
Max. lamp power	<b>50 W</b>
With light sensor	<b>Ne</b>
Suitable for suspended mounting	<b>Ne</b>
Lamp type	<b>LED</b>
Nominal voltage (V)	<b>0 - 50 V</b>
Degree of protection (IP)	<b>IP20</b>
Suitable for number of lamps	<b>1</b>
Suitable for wall mounting	<b>Ne</b>
Suitable for built-in mounting	<b>Ano</b>
Control gear included	<b>Ne</b>
Suitable for surface mounting	<b>Ne</b>
Suitable for ceiling mounting	<b>Ano</b>
Název položky	<b>Bodové svítidlo MILANO CH Max 50W IP20</b>

### Electrical characteristics

Nominal wattage	<b>max 50 W</b>
Operating voltage (V)	<b>0 - 50 V</b>
Type of Voltage	<b>AC/DC</b>

Voltage type	AC/DC
Suitable for lamp power	0 - 50 W
Lamp power at multiwatt	Ostatní
Nominal current (A)	2 A
System power	50 W
Total power (W) (light fitting)	max 50 W

#### Working conditions

Integrated driver	Ne
Light source is part of the fixture	Ne
Burning position	Libovolná
Suitable for domestic use.	Ano
Installation on flammable surfaces	Ano
Application	Všeobecné osvětlování
Lamp holder type	GU5.3
With movement sensor	Ne
Ambient temperature	-20/+50 °C
Fire resistance "D"	Ano
Fit for monitor workplace	Ano
Type of dimming	Ostatní
Emergency unit integrated	Ne
Filament test according to IEC 60695-2-10	Neuvedeno
Driver included	Ne

#### Mounting methods/application

Dimensions of installation hole	Ø65 mm
Mounting method	Vestavná

#### Physical characteristics

Dimensions (mm)	Ø80 x 28 mm
Packing method	1
Weight gross	71 g
Outer diameter	80 mm
Colour housing	Chrom
Weight netto	44 g
Built-in diameter	65 mm
Height/depth (mm)	28 mm
Material housing	Ocelový plech
Impact strength	IK10
Type of surface	Matný
Adjustability	Pevné nenastavitelné

#### Additional information

Note	Standardně dodáváno s patičí GU5,3
With lamp	Ne

#### Lighting characteristics

Light outlet	<b>Přímé</b>
Light sharing	<b>Symetrické</b>

### **Safety information**

Safety instructions	<b><a href="http://www.nbb.cz">www.nbb.cz</a></b>
Protection class	<b>Bezpečným napětím</b>

### **Exclusion of liability**

Changes to data are subject to prior notice. NBB Bohemia s.r.o. accepts no responsibility for damages caused by inaccurate interpretation of the content on this site.

### **Popis**

Rigid Spot light for halogen bulbs and LED sources. CHROME finish, G5.3 or GU10 socket.

**NBB Bohemia s.r.o., Sídliště 693, 407 22 Benešov nad Ploučnicí**  
<https://www.nbb.cz/en/> | [hotmail@nbb.cz](mailto:hotmail@nbb.cz)

Copyright CE 2024 NBB Bohemia s.r.o Všechna práva vyhrazena.