



## Product Data Sheet

Bodové svítidlo

**Spot fixture 230-240V  
TORINO WHITE**



Order number

**910000205**

Unit EAN13 code

**8595209918154**

### General information

Model/Description	<b>Bodové svítidlo</b>
Finish	<b>Vestavné pevné</b>
Brand/Manufacturer	<b>NBB</b>
Material	<b>Kov/Metal</b>
Lamp type	<b>MR16, GU10</b>
Degree of protection (IP)	<b>IP20</b>
Built-in depth	<b>70 mm</b>
Max. lamp power	<b>50 W</b>
With light sensor	<b>Ne</b>
Suitable for suspended mounting	<b>Ne</b>
Lamp type	<b>LED</b>
Nominal voltage (V)	<b>0 - 50 V</b>
Degree of protection (IP)	<b>IP20</b>
Suitable for number of lamps	<b>1</b>
Suitable for wall mounting	<b>Ne</b>
Suitable for built-in mounting	<b>Ano</b>
Control gear included	<b>Ne</b>
Suitable for surface mounting	<b>Ne</b>
Suitable for ceiling mounting	<b>Ano</b>
Název položky	<b>Bodové svítidlo TORINO WH Max 50W IP20</b>

### Electrical characteristics

Nominal wattage	<b>max 50 W</b>
Operating voltage (V)	<b>0 - 50 V</b>
Type of Voltage	<b>AC/DC</b>

Voltage type	AC/DC
Suitable for lamp power	0 - 50 W
Lamp power at multiwatt	Ostatní
Nominal current (A)	2 A
System power	50 W
Total power (W) (light fitting)	50 W

#### Working conditions

Integrated driver	Ne
Burning position	Libovolná
Suitable for domestic use.	Ano
Installation on flammable surfaces	Ano
Application	Všeobecné osvětlování
Lamp holder type	GU5.3
With movement sensor	Ne
Ambient temperature	-20/+50 °C
Fire resistance "D"	Ano
Fit for monitor workplace	Ano
Type of dimming	Ostatní
Emergency unit integrated	Ne
Filament test according to IEC 60695-2-10	Neuvedeno
Driver included	Ne

#### Mounting methods/application

Dimensions of installation hole	Ø65 mm mm
Mounting method	Vestavná

#### Physical characteristics

Dimensions (mm)	Ø88 x 26 mm
Packing method	1
Weight gross	80 g
Outer diameter	88 mm
Colour housing	Bílá
Weight netto	54 g
Built-in diameter	65 mm
Height/depth (mm)	26 mm
Material housing	Ocelový plech
Impact strength	IK10
Type of surface	Lesklý
Adjustability	Výklopné

#### Additional information

Note	Standardně dodáváno s patičí GU5,3
With lamp	Ne

#### Lighting characteristics

Light outlet	Přímé
--------------	-------

## Safety information

Safety instructions

[www.nbb.cz](http://www.nbb.cz)

Protection class

Bezpečným napětím

### Exclusion of liability

Changes to data are subject to prior notice. NBB Bohemia s.r.o. accepts no responsibility for damages caused by inaccurate interpretation of the content on this site.

## Popis

Tilttable spotlight for halogen bulbs and LED sources. WHITE finish, socket G5.3 or GU10

**NBB Bohemia s.r.o., Sídliště 693, 407 22 Benešov nad Ploučnicí**

<https://www.nbb.cz/en/> | [hotmail@nbb.cz](mailto:hotmail@nbb.cz)

Copyright © 2024 NBB Bohemia s.r.o. Všechna práva vyhrazena.