



## Product Data Sheet

LED spotlight GU10

**LED Spotlight - 7W GU10**  
**Plastic With Lens White**  
**110°, VT-2778**



Order number

**SKU1674**

Unit EAN13 code

**3800157602150**

### General information

|  |                           |
|--|---------------------------|
| Brand/Manufacturer                             | <b>V-TAC</b>              |
| Material                                       | <b>Plastic</b>            |
| Dimmable                                       | <b>Ne</b>                 |
| Energy efficiency class (canceled regulation!) | <b>A+</b>                 |
| Nominal voltage (V)                            | <b>220 - 240 V</b>        |
| Degree of protection (IP)                      | <b>IP20</b>               |
| Název položky                                  | <b>LED spotlight GU10</b> |
| Skupina produktu V-TAC                         | <b>VT-2778</b>            |

### Electrical characteristics

|                 |              |
|-----------------|--------------|
| Nominal wattage | <b>7 W</b>   |
| Frequency       | <b>50 Hz</b> |

### Working conditions

|             |                        |
|-------------|------------------------|
| Temperature | <b>-0,444444444 °C</b> |
|-------------|------------------------|

### Physical characteristics

|                      |              |
|----------------------|--------------|
| Type of chip         | <b>SMD</b>   |
| Height               | <b>50 mm</b> |
| Weight netto         | <b>50 g</b>  |
| Diameter             | <b>57 mm</b> |
| Lamp shape           | <b>PAR16</b> |
| Počet ks v balení    | <b>1</b>     |
| Barva tělesa V-TAC   | <b>White</b> |
| Počet kusů v kartonu | <b>200</b>   |

### EuP Parameters

|                                    |                          |
|------------------------------------|--------------------------|
| Number of maximal switching cycles | 15000                    |
| Rated service life                 | 20000 h                  |
| Turn-on time                       | 0.001 sec (instant on) s |
| GLS replacement                    | 45 W                     |

### Lighting characteristics

|                            |        |
|----------------------------|--------|
| Luminous flux              | 500 lm |
| Colour temperature         | 6000 K |
| Radiation angle            | 110 °  |
| Colour rendering index CRI | 80 Ra  |
| Barva světla               | White  |

### Safety information

|                       |                |
|-----------------------|----------------|
| Product certification | EMC, LVD, ROHS |
|-----------------------|----------------|

### Energetic characteristics

|                        |         |
|------------------------|---------|
| Lamp Power factor (PF) | >0.5    |
| Lamp efficacy          | 71 lm/W |

### Lamp lumen maintenance factor (LLMF)

|   |      |
|---|------|
| Lumen maintenance factor at the end of the nominal life | 70 % |
|---|------|

### Popis

NBB Bohemia s.r.o., Sídliště 693, 407 22 Benešov nad Ploučnicí  
<https://www.nbb.cz/en/> | [hotmail@nbb.cz](mailto:hotmail@nbb.cz)

Copyright CE 2024 NBB Bohemia s.r.o Všechna práva vyhrazena.