



## Product Data Sheet

LED reflektor SAMSUNG čip - záruka 5 let

**200W LED Floodlight SMD**  
**SAMSUNG CHIP Black**  
**Body Natural White, VT-**  
**200**



Order number  
**SKU418**

Unit EAN13 code  
**3800157629157**

### General information

|  |   |
|--|---|
| Brand/Manufacturer                             | V-TAC                                     |
| Material                                       | Die casting Aluminium                     |
| Dimmable                                       | Ne  |
| Energy efficiency class (canceled regulation!) | A+  |
| Nominal voltage (V)                            | 220 - 240 V                               |
| Degree of protection (IP)                      | IP65                                      |
| Název položky                                  | LED reflektory SAMSUNG čip - záruka 5 let |
| Skupina produktu V-TAC                         | VT-200                                    |

### Electrical characteristics

|                 |       |
|-----------------|-------|
| Nominal wattage | 200 W |
| Frequency       | 50 Hz |

### Working conditions

|             |                 |
|-------------|-----------------|
| Temperature | -0,444444444 °C |
|-------------|-----------------|

### Physical characteristics

|                      |                   |
|----------------------|-------------------|
| Type of chip         | SAMSUNG Chip      |
| Dimensions (mm)      | 439 x 346 x 56 mm |
| Počet ks v balení    | 1                 |
| Barva tělesa V-TAC   | Black             |
| Počet kusů v kartonu | 2                 |

### EuP Parameters

|                                    |        |
|------------------------------------|--------|
| Number of maximal switching cycles | >15000 |
|------------------------------------|--------|

|                                  |                          |
|----------------------------------|--------------------------|
| Rated service life               | 30000 h                  |
| Turn-on time                     | 0.001 sec (instant on) s |
| <b>Additional information</b>    |                          |
| Note                             | Sensor Compatibility     |
| <b>Lighting characteristics</b>  |                          |
| Luminous flux                    | 16000 lm                 |
| Colour temperature               | 4000 K                   |
| Radiation angle                  | 100 °                    |
| Colour rendering index CRI       | 80 Ra                    |
| Barva světla                     | Natural White            |
| <b>Safety information</b>        |                          |
| Product certification            | CE, EMC, ROHS            |
| <b>Energetic characteristics</b> |                          |
| Lamp Power factor (PF)           | >0.9                     |
| Lamp efficacy                    | 80 lm/W                  |
| <b>Popis</b>                     |                          |

**NBB Bohemia s.r.o., Sídliště 693, 407 22 Benešov nad Ploučnicí**

<https://www.nbb.cz/en/> | [hotmail@nbb.cz](mailto:hotmail@nbb.cz)

Copyright © 2024 NBB Bohemia s.r.o. Všechna práva vyhrazena.