



NBB Bohemia s.r.o.

Výroba a prodej osvětlovací techniky, Sídliště 693, 407 22 Benešov nad Ploučnicí



Product Data Sheet

Třípásmová lineární zářivka T5

**LT 8W T5/865 SHORT
NBB**

Order number

108009000

Unit EAN13 code

8595209901798



General information

Model/Description	Zářivková trubice
Finish	Lineární
Brand/Manufacturer	NBB
Lamp type	T5
Nominal service life (h)	12000 h
Colour	Ostatní
Socket	G5
Dimmable	Ano
Energy efficiency class (canceled regulation!)	A
Ignition strip	Ne
Fast ignition	Ne
Starter less operation	Ne
Suitable for explosion proof luminaires	Ne
Dimmable by conventional dimmers	Ne
Název položky	5 - 865
Třída energetické účinnosti podle 2019/2015	G

Electrical characteristics

Nominal wattage	8 W
Rated power (W)	8,0 W
Operating voltage (V)	56 V
Type of Voltage	AC
Lamp operating current	0,15 A
Direct connection to the mains	Ne
Lamp power	8 W

Nominal current (A)	0,15 A
Total power (W) (light fitting)	8 W

Working conditions

Ambiente temperature for max. luminous flux	35 °C
Burning position	Libovolná
Application	Emergency lighting
Application	Všeobecné osvětlení
Suitable for electronic ballast	Ano
Suitable for emergency lighting	Ano
For application at low temperatures	Ne

Physical characteristics

Dimensions (mm)	Ø16 x 288 mm
Packing method	100 - 10
Weight gross	35 g
Weight netto	30 g
Splitter protection	Ne
Tube diameter	16 mm
Lamp shape	Lineární
Length	288 mm
Internal reflector	Ne
Double-walled	Ne

EuP Parameters

Average Lifetime B50 (h)	12000 h
Luminescence Life maintenance factor	89,0 %
Number of maximal switching cycles	>30000 /warm start
The rate of premature failures	<1 %
Rated service life	12000 h
Energy consumption (AGGR)	8 kWh/1000h

Lighting characteristics

Type of spectrum	Třípásmové
Color rendering	1B
Light Colour	chladná denní
Dominant wavelength	544 nm
Luminous flux	420 lm
Colour temperature	6500 K
Colour rendering index CRI	84 Ra
Full spectrum lamps	Ne
Colour of light	865
Colour of light acc. EN 12464-1	Cool >5300 K
Beam angle Degrees (°)	360 °
Chromaticity coordinates x	0,341
Chromaticity coordinates y	0,323

Safety information

Safety instructions	www.nbb.cz
---------------------	--

Environmental characteristics

Mercury content	5,00 mg
-----------------	---------

Energetic characteristics

Rated efficiency after 100h	99,99 %
Lamp efficacy	53 lm/W

Lamp survival factor (LSF)

LSF after 2.000 hrs	99 %
LSF after 4.000 hrs	90,0 %
LSF after 8.000 hrs	84 %
LSF after 10.000 hrs	70 %

Lamp lumen maintenance factor (LLMF)

LLMF after 2.000 hrs	90 %
LLMF after 4.000 hrs	80 %
LLMF after 8.000 hrs	70 %
LLMF after 10.000 hrs	60 %

Exclusion of liability

Changes to data are subject to prior notice. NBB Bohemia s.r.o. accepts no responsibility for damages caused by inaccurate interpretation of the content on this site.

Warning

If broken in a closed room, we recommend ventilation to reduce the mercury vapor concentration. Use protective equipment while working. Immediately remove the shards so that they do not get injured. After removing the shards, use the technical means for decontamination of mercury. For this purpose we supply decontamination kits, which you can order by phone or in our internet shop. The decontamination kit should not be missed especially in plants where there is a danger of breaking light sources containing mercury, such as stores, warehouses, but can also be used in households. In case of nausea, give first aid and call a physician.


Notice

Fluorescent tubes of all types require a corresponding type of ballast to operate. A suitable ballast type can be found in the detail of the item (additional products). The quality and type of the ballast greatly affect the life of the fluorescent lamp. NBB Bohemia is not responsible for shortening lamp life when the fluorescent lamp is connected to a ballast type that NBB Bohemia s.r.o. because in such a case we can not guarantee the suitability of using the ballast to the supplied fluorescent tube. When directly connected to the mains voltage without using the ballast, the fluorescent lamp will be destroyed. Fluorescent tubes are not suitable for connection to motion sensors or for connection to frequent switching devices. Frequent switching causes shortening of lamp life. Frequent switching is considered to switch the fluorescent lamp to an interval of less than 20 minutes.

Popis

Tri-band fluorescent tube T5 8W cool daylight for general lighting.

Technical drawing



NBB Bohemia s.r.o., Sídliště 693, 407 22 Benešov nad Ploučnicí
<https://www.nbb.cz/en/> | hotmail@nbb.cz

Copyright CE 2024 NBB Bohemia s.r.o. Všechna práva vyhrazena.