



Product Data Sheet

Žárovka pro digestoře

ADR 240V 40W E14
CLEAR RESISTA Lamp for
cooker hoods (digestors)
240V 40W E14



Order number

368010000

Unit EAN13 code

8595209900944

General information

Model/Description	Vláknová žárovka
Finish	Pro digestoře
Brand/Manufacturer	NBB
Nominal service life (h)	1000 h
Nominal voltage (V)	24 V
Model	Čirá
Socket	E14
Energy efficiency class (canceled regulation!)	E
Shock-proof	Ne
Krypton	Ne
Nominal voltage (V)	230 - 240 V
Multi-coiled filament	Ano
Lamp voltage	230 - 240 V
Dimmable by conventional dimmers	Ano
Název položky	ADR 240V 40W E14 CLEAR RESISTA
Třída energetické účinnosti podle 2019/2015	G

Electrical characteristics

Nominal wattage	40 W
Rated power (W)	38,9 W
Operating voltage (V)	220 - 240 V
Type of Voltage	AC/DC
Direct connection to the mains	Ano
Nominal current	160 mA
Lamp power	40 W

Voltage type	AC/DC
Nominal current (A)	1,05 A
Total power (W) (light fitting)	40 W
Working conditions	
Bulb temperature (max.)	250 °C
Cap temperature (max.)	200 °C
Burning position	Libovolná
Suitable for domestic use.	Ne
Application	Elektrické spotřebiče
Suitable for baking oven	Ne
Suitable for refrigerator	Ano
Special application	Ostatní
Physical characteristics	
Dimensions (mm)	Ø25 x 82 mm
Packing method	1 - 10
Weight gross	15 g
Weight netto	8 g
Total length	82 mm
Diameter	25 mm
Splitter protection	Ne
Lamp shape	A55
Filament shape	CoiledCoil
Carbon filament	Ne
With vacuum	Ne
Number of filament supports	5
Fuses	1
EuP Parameters	
Average Lifetime B50 (h)	1000 h
Luminescence Life maintenance factor	80,0 %
The rate of premature failures	<1 %
Rated service life	1000 h
Energy consumption (AGGR)	40 kWh/1000h
Lighting characteristics	
Color rendering	1A
Luminous flux	400 lm
Colour temperature	2580 K
Colour rendering index CRI	100 Ra
Beam angle Degrees (°)	330 °
Chromaticity coordinates x	0,469
Chromaticity coordinates y	0,414
Safety information	
Safety instructions	www.nbb.cz

Environmental characteristics

Mercury content	0,00 mg
-----------------	---------

Energetic characteristics

Lamp efficacy	9,2 lm/W
---------------	----------

Lamp displacement factor (DF)	1,00
-------------------------------	------

Lamp survival factor (LSF)

LSF after 100 hrs	99,0 %
-------------------	--------

LSF after 1.000 hrs	50,0 %
---------------------	--------

Exclusion of liability

Changes to data are subject to prior notice. NBB Bohemia s.r.o. accepts no responsibility for damages caused by inaccurate interpretation of the content on this site.

Popis

Clear tubular lamps for kitchen hoods.

NBB Bohemia s.r.o., Sídliště 693, 407 22 Benešov nad Ploučnicí

<https://www.nbb.cz/en/> | hotmail@nbb.cz

Copyright CE 2024 NBB Bohemia s.r.o Všechna práva vyhrazena.