



## Product Data Sheet

Nízkovoltová žárovka čirá

**AGN 24V A55 40W E27  
CLEAR**



Order number

**339002000**

Unit EAN13 code

**8595209901026**

### General information

Model/Description	<b>Žárovka/Incandescent lamps</b>
Finish	<b>Čirá/Clear</b>
Brand/Manufacturer	<b>NBB</b>
Nominal service life (h)	<b>1000 h</b>
Nominal voltage (V)	<b>24 V</b>
Model	<b>Čirá</b>
Socket	<b>E27</b>
Energy efficiency class (canceled regulation!)	<b>E</b>
Shock-proof	<b>Ano</b>
Krypton	<b>Ne</b>
Nominal voltage (V)	<b>24 V</b>
Multi-coiled filament	<b>Ano</b>
Lamp voltage	<b>24 V</b>
Dimmable by conventional dimmers	<b>Ano</b>
Název položky	<b>AGN 24V A55 40W E27 ČIRÁ</b>
Třída energetické účinnosti podle 2019/2015	<b>G</b>

### Electrical characteristics

Nominal wattage	<b>40 W</b>
Rated power (W)	<b>40 W</b>
Operating voltage (V)	<b>22 - 24 V</b>
Type of Voltage	<b>AC/DC</b>
Direct connection to the mains	<b>Ne</b>
Lamp power	<b>40 W</b>
Voltage type	<b>AC/DC</b>

Nominal current (A)	1,67 A
Total power (W) (light fitting)	40 W

### Working conditions

Bulb temperature (max.)	200 °C
Cap temperature (max.)	150 °C
Burning position	Libovolná
Suitable for domestic use.	Ne
Application	Průmyslové aplikace
Suitable for baking oven	Ne
Suitable for refrigerator	Ne
Special application	Ostatní

### Physical characteristics

Dimensions (mm)	Ø55 x 98 mm
Packing method	1 - 100
Weight gross	30 g
Weight netto	20 g
Total lenght	98 mm
Diameter	55 mm
Splitter protection	Ne
Lamp shape	Ostatní
Carbon filament	Ne
Number of filament supports	5

### EuP Parameters

Average Lifetime B50 (h)	1000 h
Luminescence Life maintenance factor	80,0 %
The rate of premature failures	<2 %
Rated service life	1000 h
Energy consumption (AGGR)	40 kWh/1000h

### Lighting characteristics

Color rendering	1A
Luminous flux	415 lm
Colour temperature	2700 K
Colour rendering index CRI	100 Ra
Chromaticity coordinates x	0,460
Chromaticity coordinates y	0,410

### Safety information

Safety instructions	<a href="http://www.nbb.cz">www.nbb.cz</a>
---------------------	--

### Environmental characteristics

Mercury content	0,00 mg
-----------------	---------

### Energetic characteristics

Lamp efficacy	<b>8 lm/W</b>
Lamp displacement factor (DF)	<b>1,00</b>
<b>Lamp survival factor (LSF)</b>	
LSF after 100 hrs	<b>99,0 %</b>
LSF after 1.000 hrs	<b>50,0 %</b>
<b>Exclusion of liability</b>	

Changes to data are subject to prior notice. NBB Bohemia s.r.o. accepts no responsibility for damages caused by inaccurate interpretation of the content on this site.

#### **Popis**

Industrial 24V incandescent lamps for general lighting. Lifespan 1.000 h.

**NBB Bohemia s.r.o., Sídliště 693, 407 22 Benešov nad Ploučnicí**  
<https://www.nbb.cz/en/> | [hotmail@nbb.cz](mailto:hotmail@nbb.cz)

Copyright CE 2024 NBB Bohemia s.r.o Všechna práva vyhrazena.